

CALGON CARBON CORP -- ACTIVATED CARBON 31025 -- 4610-00-363-5770

===== Product Identification =====

Product ID:ACTIVATED CARBON 31025  
MSDS Date:11/01/1982  
FSC:4610  
NIIN:00-363-5770  
MSDS Number: BJFNZ  
=== Responsible Party ===  
Company Name:CALGON CARBON CORP  
Address:120 E OGDEN AVE  
City:HINSDALE  
State:IL  
ZIP:60521-3579  
Country:US  
Info Phone Num:312-787-6789  
Emergency Phone Num:312-787-6700  
CAGE:1D  
A66

=== Contractor Identification ===

Company Name:BARNSTEAD/THERMOLYNE CORP, DIV OF SYBRON CORP  
Address:2555 KERPER BLVD  
Box:City:DUBUQUE  
State:IA  
ZIP:52001-1461  
Country:US  
Phone:800-446-6060/ FAX: 319-589-0516  
CAGE:05852  
Company Name:CALGON CARBON CORPORATION  
Address:400 CALGON CARBON DR  
Box:717  
City:PITTSBURGH  
State:PA  
ZIP:15230-0717  
Country:US  
Phone:412-787-6700  
CAGE:1DA66

===== Composition/Information on Ingredients =====

Ingred Name:CARBON

===== Hazard

s Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:CARBON DUST MAY CAUSE TEMPORARY RESPIRATORY DISCOMFORT.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:INHALE:RESPIRATORY DISCOMFORT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid

Measures =====

First Aid:EYE:FLUSH WITH COPIOUS QUANTITIES OF WATER FOR 15 MINUTES, CALL MD. SKIN:WASH THOROUGHLY WITH WATER. INHALE:REMOVE TO FRESH AIR, GET MD. INGEST:GET MD.

===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEMICAL, CO\*2, WATER SPRAY, FOAM, WATER FOG OR SAND/EARTH.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM OR SWEEP UP SPILLED MATERIAL;AVOID CREATING DUST.CONSIDER POTENTIAL HAZARDS OF ANY ABSORBED MATERIAL BEFORE DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. STORE IN DRY PLACE. DO NOT ENTER VESSELS CONTAINING

ACTIVATED CARBON BEFORE CHECKING OXYGEN LEVEL.

Other Precautions:IF NECESSARY, USE NIOSH/MSHA APPROVED SCBA.

ELECTRICAL EQUIPMENT SHOULD BE PROTECTED FROM CARBON DUSTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NORMAL TO MAINTAIN DUST BELOW TLV (10MG/M\*3).

Protective Gloves:NONE REQUIRED.

Eye Protection:CHEMICAL WORKERS GOGGLES.

Other Protective Equip

ment:NONE REQUIRED.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

THIS IS NOT A KIT. THIS IS PART C OF A THREE PART SINGLE PRODUCT.

===== Physical/Chemical Properties =====

Spec Gravity:1.8-2.1

pH:5.-8.

Appearance and Odor:BLACK GRANULES, ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:CO\*2, C

O

Hazardous Decomposition Products:CO\*2, CO

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF MATERIAL, ITS RINSINGS OR SPILL  
RESIDUES MUST BE I/A/W FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this inform

ation to be accurate and

disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.