View NSN Online: https://aerobasegroup.com/nsn/6850-00-559-2836

Product ID:CLEANING COMPOUND, SOLVENT P-C-444B TY I MSDS Date:07/18/1988 FSC:6850 NIIN:00-559-2836 **MSDS Number: BJKNX** === Responsible Party === Company Name: OCTAGON PROCESS INC. Address:596 RIVER ROAD City:EDGEWATER State:NJ ZIP:07020 Country:US Info Phone Num:201-945-9400 Emerg ency Phone Num:201-945-9400 CAGE:82925 === Contractor Identification === Company Name: OCTAGON PROCESS INC. Address:596 RIVER ROAD Box:City:EDGEWATER State:NJ ZIP:07020 Country:US Phone:201-945-9400 CAGE:82925

Ingred Name:PETROLEUM DISTILLATE CAS:8002-05-9 RTECS #:SE7449000 Fraction by Wt: 90%

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports

of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITATION TO SKIN AND EYES, MUCOUS MEMBRANES. HIGH VAPOR CONCENTRATIONS CAN CAUSE CNS DEPRESSION. PROLONG SKIN CONTACT CAN CAUSE DERMATITIS LIKE CONDITIONS. Effects of Overexposure:EYES: TEARING AND SLIGHT BURNING SENSATION. SKIN: DEFATTING AND REDNESS. INHALATION: HEADACHE, DIZZINESS, WEAKNESS AND LOSS OF COORDINATION. Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

====== F irst Aid Measures ======== F

First Aid:SKIN: WASH AREA WITH MILD SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL AID. EYES: FLUSH WITH WATER FOR 15 MINUTES IF IRRITATION PERSISTS, GET MEDICAL AID. INHALATION: REMOVE TO FRESH AIR. TREAT S YMPTOMATICALLY. IF INGESTED: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:158 F/70 C Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures:USE PROPER PROTECTIVE EQUIPMENT IN ENCLOSED OR CONFINED AREAS. KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER SPRAY. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. DIKE AREA TO CONTAIN. SMALL SPILLS SHOULD BE ABSORBED ON SUITABLE MEDIA & PLACED IN DISPOSAL CONTAINERS. DO NOT ALLOW PRODUCT TO ENTER WATERCOURCES.

=====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. KEEP AWAY FROM STRONG OXIDIZING MATERIALS. STORE AWAY FROM OPEN FLAMES, SPARKS, ETC. KEEP CONTAINERS CLOSED WHEN NOT IN USE.
Other Precautions:LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. DO NOT RE-USE EMPTY CONTAINERS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IN CONFINED AREAS, ORGANIC VAPOR RESPIRATORS. Ventila

tion:LOCAL EXHAUST
Protective Gloves:RUBBER, NEOPRENE.
Eye Protection:CHEMICAL SAFETY GOGGLES &/OR FACE SHIELD
Other Protective Equipment:AS NEEDED TO AVOID SKIN &/OR EYE CONTACT. EYE WASH FOUNTAIN. SAFETY SHOWER.
Work Hygienic Practices:WASH HANDS AND FACE AFTER USING AND BEFORE EATING, DRINKING OR USING TOILET FACILITIES.
Supplemental Safety and Health
LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. DO NOT RE-USE.

Boil

ing Pt:B.P. Text:456 F/236C Spec Gravity:0.87 @ 77 F Solubility in Water:NEGLIGIBLE Appearance and Odor:AMBER COLORED LIQUID, PETROLEUM LIKE ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING MATERIALS. Stability Condition to Avoid:OPEN FLAMES, SPARKS, HIGH ENERGY SOURCES.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND

FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this i nformation to their particular situation.