

DYKEM COMPANY -- LAYOUT FLUIDS,DYKEM, OPAQUE SERIES -- 6850-00-663-0114
===== Product Identification =====

Product ID:LAYOUT FLUIDS,DYKEM, OPAQUE SERIES

MSDS Date:06/01/1989

FSC:6850

NIIN:00-663-0114

MSDS Number: BJKXQ

=== Responsible Party ===

Company Name:DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST. LOUIS

State:MO

ZIP:63114-5905

Country:US

Info Phone Num:314-423-0100

Emergency Phone Num:31

4-423-0100

CAGE:EO153

=== Contractor Identification ===

Company Name:DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST. LOUIS

State:MO

ZIP:63114-5905

Country:US

Phone:314-423-0100

CAGE:EO153

Company Name:ITW DYKEM/ DYMON

Address:805 E OLD 56 HWY

Box:City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:800-443-9536

CAGE:98148

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 30-40%

Other REC Limi

ts:NONE SPECIFIED
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 50-60%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 3-6%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred
Name:COLLODION (CELLULOSE NITRATE (PROPORTIONAL 70/30 WITH
ISOPROPYL ALCOHOL)
CAS:9004-70-0
RTECS #:QW0970000
Fraction by Wt: 2.1-4.2%
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 0.9-1.8%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 5000 MG/KG (TOLUENE)
Routes of En

try: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. OVEREXPOSURE MAY RESULT IN LIGHTHEADEDNESS AND STAGGERING GAIT. IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. CHRONIC: REPORTS H AVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NONE O F THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. OVEREXPOSURE MAY RESULT IN FATIGUE, WEAKNESS, CONFUSION EUPHORIA, DIZZINESS, HEADACHE, DILATED PUPILS, LACRIMATION, NERVOUSNESS, MUSCLE FATIGUE, INSOMNIA, PARESTHESIA, DERMATITIS, AND PHOTOPHOBIA.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, RESPIRATORY TRACT OR NERVOUS SYSTEM MAY BE AT INCREASED RISK FROM EXPOSURE. DRYING/CRACKING OF SKIN.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING EYELID. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ADVICE. INHALATION: REMOV E TO FRESH AIR. GIVE MOUTH-TO-MOUTH RESUSCITATION IF NOT BREATHING. GET MEDICAL ATTENTION. IN GESTION: DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:53.0F,11.7C
Autoignition Temp:Autoignition Temp Text:UNKNON
Lower Limits:1.4
Upper Limits:11.2
Extinguishing Media:CARBON DIOXIDE, REGULAR FOAM, DRY CHEMICAL
Fire Fighting Procedures:WEAR SCBA IN ENCLOSED AREAS. WATER MAY BE USED TO COOL FIRE-EXPOSED CONTAINERS.
Unusual Fire/

Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MOVE THROUGH THE VENTILATION SYSTEM AND BE INGNITED BY REMOTE SPARKS OR IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:CONTENTS ARE FLAMMABLE. KEEP AWAY FROM HE

AT, SPARKS, AND OPEN FLAME. DURING USE AND UNTIL ALL VAPORS ARE GONE: KEEP AREA VENTILATED-DO NOT SMOKE.

Other Precautions:AVOID BREATHING OF VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED RESPIRATOR IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL/TLV. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXH AUST ACCEPTABLE IF THE

EXPOSURE IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves:NEOPRENE OR NATURAL RUBBER GLOVES

Eye Protection:PAINT GOGGLES/SAFETY GLASSES AS REQUIRED

Other Protective Equipment:INDUSTRIAL-TYPE WORK CLOTHING, HAT AND APRON AS REQUIRED.

Work Hygienic Practices:USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR/SPRAY MIST. AVOID CONTACT WITH SKIN & EYES. WASH HANDS AFTER USE.

Supplemental Safety and Health

KEEP CONTAINER CLOSED WHEN NOT IN USE

. TRANSFER ONLY TO APPROVED

CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. USE APPROVED BONDING AND GROUNDING PROCEDURES. THIS IS PART B UNDER THIS NSN. (DIFFERENT FORMULATION FROM PART A)

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=71.1C, 160.F

Vapor Pres:36

Vapor Density:>1

Spec Gravity:0.86

pH:UNKNON

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in

Water:APPRECIABLE

Appearance and Odor:INTENSE COLOR, SWEET SOLVENT ODOR

Percent Volatiles by Volume:UNKNON

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:AVOID HEAT SPARKS AND OPEN FLAME

Hazardous Decomposition Products:BY FIRE: CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MATERIAL WILL LI

KELY BE A LAND-BANNED

HAZARDOUS WASTE WHICH MUST BE DISPOSED OF ACCORDINGLY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability fo

r its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.