

PRATT AND LAMBERT INC -- ENAMEL ALKYD GLOSS BROWN 10049 ID742006 -- 8010-00-298-2293
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS BROWN 10049 ID742006
MSDS Date:08/23/1990
FSC:8010
NIIN:00-298-2293
MSDS Number: BJLGH
=== Responsible Party ===
Company Name:PRATT AND LAMBERT INC
Address:16116 E 13TH ST
Box:2153
City:WICHITA
State:KS
ZIP:67201
Country:US
Info Phone Num:316-733-136

1
Emergency Phone Num:716-873-6000 DOT EMER 8002553924
Preparer's Name:W.A. ELLISON
CAGE:61196

=== Contractor Identification ===
Company Name:PRATT AND LAMBERT INC
Box:6027
City:CLEVELAND
State:OH
ZIP:44101-1027
Country:US
Phone:216-566-2902
CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (VP 2 MMHG @ 20C)
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 45%
Other REC Limits:LFL 1.0 UFL 7.0
OSHA PEL:100 PPM/525 MG/CU.M.
ACGIH TLV:100

PPM/525 MG/CU.M.

Ingred Name:VOC 3.94 LB/GAL LESS WATER & NPRS* 473 G/L LESS WATER
CALCULATED

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 10.10 LB/GAL SOLIDS 1212 G/L SOLIDS CALCULATED

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED
PROLONGED/REPEATED OCCUPATIONAL OVEREXPOSURE TO
SOLVENTS WITH

PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL
OR FATAL.

Explanation of Carcinogenicity:NONE CURRENTLY KNOWN.

Effects of Overexposure:SWALLOW: CAN CAUSE GASTRO IRRIT, NAUSEA &
VOMITING. ASPIRATION INTO LUNGS MAY CAUSE CHEM PNEUMONITIS WHICH
CAN BE FATAL. INHALED:NOSE OR THROAT IRRIT. HIGH CONCENTRATE MAY
CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY
HEADAC

HES, DIZZ, NAUSEA & CONFUSION. EYES: IRRIT. SKIN:MAY CAUSE
DEFATTING & IRRIT.

=====
===== First Aid Measures =====

First Aid:SWALLOW:DO NOT INDUCE VOMIT. CALL PCC/HOSPITAL/PHYSICIAN
IMMED. INHALED:REMOVE TO FRESH AIR IMMED. IF BREATH STOPPED, GIVE
CPR. KEEP WARM/QUIET. GET MED ATTN IMMED. EYES:FLUSH W/H2O, LIFTING
LIDS FOR 15 MINS. GET MED ATTN. SKIN:REMOVE CONTAM CLOTHES. WASH
AFFECTED AREA W/SOAP & H2O. OBTAIN MED ATTN IF IRRIT PERSIST. N

OTE
TO PHYSICIAN:DIRECT TREATMENT AT CONTROL OF SYMPTOMS & CLINICAL
CONDITIONS.

=====
===== Fire Fighting Measures =====

Flash Point:>102 F/>39 C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS DESIGNED FOR
FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:USE WATER TO COOL EXPOSED CONTAINERS TO
PREVENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION FROM EXTREME HEAT.
IF WATER USED, FOG NOZZLES ARE PREFERE

RRABLE.

Unusual Fire/Explosion Hazard:OVEREXPOS TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY BE DELAYED, OBTAIN MED. KEEP CONTAIN TIGHTLY CLOSED. CONTAINER MAY EXPLODE FROM EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM IGNITE SOURCES. DIKE & CONTAIN W/MATERIAL(E.G. SAND,ETC)TRANSFER LIQ TO COVERED METAL CONTAIN FOR RECOVERY/DISPOSAL. REMOVE W/INERT ABSORB. USE ONLY NON-SPARK

TOOLS. PREVENT CONTAM OF SEWERS,GROUNDWATERS W/MATERIAL/ABSORB

Neutralizing Agent:N/K.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 95F. STORE LARGE AMOUNTS IN COMPLIANCE W/OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

Other Precautions:EMPTY CONTAINERS MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPT Y. DRUM IS NOT A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTED AREA MAY NOT REQUIRE USE OF RSPRTR. RESTRICTED VENT:CHEM CARTRIDGE RSPRTR MAYBE REQUIRED. SPRAY:USE MECH PREFILTER. CONFINED AREA:USE AIR SUPPLIED RSPRTR. IF TLV EXCEED USE PROPERLY FITTED RSPRTR W/PROTECTION FACTOR

Ventilation:GEN DILUTE/LOCAL EXHAUST IN VOL/PATTERN TO KEEP CONC ENTRATE

OF HAZARD INGRED BELOW LOWEST LIMITS. REMOVE DECOMP PRODUCTS

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED AS HAZARDOUS WASTE BASED ON ITS IGNITABILITY CHARACTERISTIC, I.E. HAS A FLASH POINT OF 140 DEG. F. OR LES

S. THE PROPER RCRA CLASSIFICATION WOULD BE D001.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:302 TO 390F

Vapor Density:> THAN AIR

Spec Gravity:1.0

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES

OF

IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS, FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOS

AL OF

FLAMMABLE MATERIALS. CONTAMINATED ABSORB MAY BE DISPOSED IN HAZARD WASTE LANDFILL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.