

CHEMICAL SPECIALISTS & DEVELOPMENT -- THINNER, PAINT TYPE III-ODORLESS --
8010-01-021-3320

===== Product Identification =====

Product ID:THINNER, PAINT TYPE III-ODORLESS
MSDS Date:09/01/1990
FSC:8010
NIIN:01-021-3320
MSDS Number: BJMGX
=== Responsible Party ===
Company Name:CHEMICAL SPECIALISTS & DEVELOPMENT
Address:#5 HACKBERRY LANE
City:CUT & SHOOT
State:TX
ZIP:77303
Country:US
Info Phone Num:40
9-756-1065
Emergency Phone Num:800-424-9300
Preparer's Name:DAVID SHIPP
CAGE:CHEMS
=== Contractor Identification ===
Company Name:CHEMICAL SPECIALISTS INC
Address:149 WEST TRIGG AVE
City:HARRISBURG
State:NC
ZIP:28075
Country:US
Phone:704-522-0825
CAGE:CHEMS
Company Name:CSD INC. (PRE 1985 NAME: MATHEWS, INC)
Address:420 SEABOARD DRIVE
Box:City:MATTHEWS
State:NC
ZIP:28105-5073
Country:US
Phone:704-821-9822
CAGE:5W216

===== Composition/Information on Ingredients =====

Ingred Na

me:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:ASPIRATION OF MATERIAL INTO THE LUNGS
CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
Effects of Overexposure:EYES:MAY CAUSE IRRIT, REDNESS, TEARING.
SKIN:PROLONGED/REPEATED CONTACT C
AN CAUSE MOD IRRIT, DEFATTING,
DERMATITIS. EXCESSIVE INHALE:NASAL & RESPIRATORY IRRIT, CENTRAL
NERVOUS SYST EFFECTS, DIZZI, WEA K, FATIGUE, NAUSEA, HEADACHES &
POSSIBLE UNCONSC & EVEN DEATH. SWALLOW:GASTROINTESTINAL IRRIT,
NAUSEA, VOMIT & DIARRHEA

===== First Aid Measures =====

First Aid:SKIN:THORO WASH AREA W/SOAP & WTR. REMOVE CONTAM CLOTHES.
LAUNDER CLOTHES BEFORE RE-USE. DISCARD SATURATED SHOES. EYES:FLUSH
W/LG AMNTS OF WTR, LIF
TING LIDS, GET MED ATTN. SWALLOWED:DO NOT
INDUCE VOMI T, KEEP PERSON WARM/QUIET, GET MED ATTN. ASPIRATION
INTO LUNG DUE TO VOMITING CAN CAUSE CHEM PNEUMONITIS, CAN BE FATAL.
INHALE:REMOVE TO FRESH AIR, ADMIN CPR/OXYGEN AS NEEDED, KEEP
WARM/QUIET, GET MED

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:140 F/60 C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL
Fire Fighti

ng Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES.

Unusual Fire/Explosion Hazard:VAPOR > THAN AIR & MAY TRAVEL ALONG GROUND/MOVED BY VENT & IGNITED BY HEAT, PILOT LIGHT, OTHER IGNITE SOURCES AT DISTANT LOCATIONS. EMPTY CONTAINER CAN EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SM:ABSORB LIQ ON PAPER,VERMICUL,FLOOR

ABSORB,TRANSFER TO HOOD.LG:ELIM IGNITE SOURCES.REMOVE PERSONS NOT WEAR PROTECTIVE EQUIP.STOP SPILL AT SOURCE.DIKE AREA, PREVENT SPREAD, PUMP LIQ TO SALVAGE TANK, TAKE UP REMAIN W/SAND, ETC.SHOVEL TO CONTAINERS*

Neutralizing Agent:N/K. *PREVENT RUN-OFF TO SEWERS OR ANY BODIES OF WTR. NOTIFY AUTHORITY IF ENTERS

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS OF MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTY
RETAINS RESIDUES(VAPOR, LIQ, SOLID)ALL HAZARD PRECAUTIONS GIVEN MUST BE OBSERVED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE LIMIT/COMPONENT IS EXCEEDED:NIOSH/MSHA APPROVED AIR SUPPLIED RSPRTR, IF NO ENVIRON CONTROL. OSHA REGS PERMIT OTHER NIOSH/MSHA RSPRTR(NEG PRESS TYPE)UNDER SPECIFIED CONDITIONS(SEE SAFETY EQ UIP SUPPLIER & ENGINEER/ADMIN CONTROLS)

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST)
VENT TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RESISTANT GLOVES SUCH AS NITRILE RUBBER

Eye Protection:CHEM SPLASH GOGGLES OR SAFETY GLASSES

Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WEAR IMPERVIOUS CLOTHING AND BOOTS.

Supplemental Safety and Health

SEE FILE FOR ADDITIONAL INFORMATION.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:360 F/182 C

Melt/Freeze Pt:M.P/F.P Text:-20F,-29C

Vapor Pres:.05

MMHG
Vapor Density:5.17
Spec Gravity:0.740
Evaporation Rate & Reference:.03 (ETNYL ETHER=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR, LITTLE IF ANY COLOR; SLIGHT OIL ODOR.
Percent Volatiles by Volume:100
Corrosion Rate:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON
DIOXIDE AND CARBON MONOXIDE,
VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:SM:ALLOW VOLATILE PORTION TO EVAPORATE IN
HOOD.ALLOW VAPOR TO COMPLETELY CLEAR HOOD DUCT.DISPOSE REMAINING
MATERIAL IN ACCORD W/APPLICABLE REGS.LG:DESTROY BY LIQ
INCINERATE.CONTAM ABSORB MAY BE DEPOSITED IN LANDFILL IN ACCORD
W/LOCAL,STATE& FED REGS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use
by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.