

HONEYMEAD PRODUCTS CO. -- BOILED LINSEED OIL -- 8010-00-152-3245

=====  
Product Identification  
=====

Product ID:BOILED LINSEED OIL

MSDS Date:01/01/1987

FSC:8010

NIIN:00-152-3245

MSDS Number: BJMWH

=== Responsible Party ===

Company Name:HONEYMEAD PRODUCTS CO.

Address:25-44TH AVENUE N.E.

City:MINNEAPOLIS

State:MN

ZIP:55421

Country:US

Info Phone Num:612-925-1127

Emergency Phone Num:612-925-1127

CAGE:

KO328

=== Contractor Identification ===

Company Name:HONEYMEAD PRODUCTS CO.

Address:25-44TH AVENUE N.E.

City:MINNEAPOLIS

State:MN

ZIP:55421

Country:US

Phone:612-925-1127

CAGE:KO328

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON-HAZARDOUS INGREDIENT

Other REC Limits:NONE SPECIFIED

=====  
Fire Fighting Measur

es =====

Flash Point Method:CC

Flash Point:>250 F/121 C

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:MUST USE A BLANKETING OR SMOTHERING TYPE OF EXTINGUISHING MATERIAL. DO NOT USE WATER.

Unusual Fire/Explosion Hazard:BEING LIGHTER THAN WATER, DO NOT USE WATER TO EXTINGUISH FIRES.

===== Accidental Release Measures =====

Spill Release Procedures:AS IN ANY TANK STORAGE, DAMS TO CONTAIN LEAKING OR RUPTURED

TANKS ARE RECOMMENDED. IF NOT PRESENT, ANY SPILL OR LEAK CAN FURTHER BE CLEANED WITH WATER & TRISODIUM PHOSPHATE OR SODA ASH & WATER.

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS NEEDED. IF STORED OUTSIDE, TANKS SHOULD BE COVERED TO PREVENT CONTAMINATIONS WITH WATER, DIRT AND ETC.

===== Exposure Controls/Personal Protection =====

Protective Gloves:NOT NECESSARY

Eye Protection:GOG

GLASSES RECOMMENDED

Other Protective Equipment:NOT NECESSARY

Supplemental Safety and Health

BOILED LINSEED OIL IS NOT A HAZARDOUS MATERIAL UNDER THE CURRENT DEPT. OF LABOR DESIGNATIONS. HOWEVER, RAGS OR WASTE CONTAINING LINSEED OIL THAT PRESENT A LARGE AIR-OIL INTERFACES WILL OXIDIZE AND CAN IGNITE SPONTANEOUSLY AND SHOULD BE HANDLED WITH CARE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:600 F/316 C

Vapor Pres:0.001 @250C

Spec Gravity:0.92

3-0.938@25C

Solubility in Water: