

PRATT & LAMBERT INC -- LAC SPRAYING WHITE 17875 ID 793716 -- 8010-00-161-7337

=====  
Product Identification  
=====

Product ID:LAC SPRAYING WHITE 17875 ID 793716

MSDS Date:08/21/1990

FSC:8010

NIIN:00-161-7337

MSDS Number: BJMWQ

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733-1361

Pre

parer's Name:W. A. ELLISON

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 25

%  
Other REC Limits:LFL 2.0/UFL 11.0  
OSHA PEL:150 PPM  
ACGIH TLV:150 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 5%  
Other REC Limits:LFL 3.0/UFL 13.0  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE  
CAS:9004-70-0  
RTECS #:QW0975100  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOBUTYL ALCOHOL (SARA III)  
CAS:78-83-1  
RTECS #:NP9625000  
Fraction by Wt:  
10%  
Other REC Limits:LFL 1.0/UFL 11.0  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 5%  
Other REC Limits:LFL 1.0/UFL 7.0  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000

LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: < 5%  
Other REC Limits:LFL 1.0/UFL 6.7  
OSHA PEL:100 PPM/125 STEL  
ACGIH TLV:100 PPM/125STEL 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)  
CAS:117-81-7  
RTECS #:TI0350000  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3/10 STEL  
ACGIH TLV:5 MG/M3; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 5%  
Other REC Limits:LFL 1.7/UFL 7.1  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA  
CAS:8030-30-6  
RTECS #:DE3030000  
Fraction by Wt: 5%  
Other REC Limits:LFL .9/UFL 6.7  
OSHA PEL:300 PPM/400 PPM STEL  
ACGIH TLV:300 PPM/1350 MG/CU.M

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 10%  
Other REC

Limits:LFL 2.0/UFL 10.0  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOC 5.53 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY  
REACTIVE MATERIALS 664 G/L LESS WATER

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 28.73 LB/GAL SOLIDS 3448 G/L SOLIDS

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES

Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SWALLOWING MAY CAUSE GASTROINTESTINAL  
IRRIT & CHEMICAL PNEUMONITIS. INHALATION MAY CAUSE NOSE/THROAT  
IRRITATION. EYE & SKIN IRRITANT; MAY CAUSE SKIN DEFATTING. OTHER  
EFFECTS: INJURY TO LIVER, KIDNEYS, & BLOOD, PERMANENT BRAIN &  
NERVOUS SYSTEM DAMAGE & DEATH.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS  
A POTENTIAL CARCINOGEN BY THE NATIONAL TOXICOLO  
GY PROGRAM.

Effects of Overexposure:HEADACHES, DIZZINESS, NAUSEA, VOMITING,  
CONFUSION & SEVERE IRRITATION REACTION IF PRODUCT IS SWALLOWED,  
INHALED, ABSORBED THROUGH SKIN, OR GETS INTO EYES.

Medical Cond Aggravated by Exposure:REPORTS HAVE ASSOCIATED PROLONGED  
AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT  
BRAIN AND NERVOUS SYSTEM DAMAGE.

===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. CALL PO  
ISON CONTROL

CENTER IMMED. INHALATION: REMOVE TO FRESH AIR IMMED. IF BREATHING  
STOPPED, GIVE CPR & KEEP WARM. EYE: FLUSH W/LRG AMTS OF WATER FOR  
15 MIN LIFTI NG UPPER/LOWER LIDS CONTINUOUSLY. SKIN:IMMEDIATELY  
FLUSH CONTAMINATED AREA W/LRG AMTS OF WATER. REMOVE CONTAMINATED  
CLOTHES AS WATER IS APPLIED. GET MEDICAL ATTN IMMED FOR ANY OF  
THESE CONDITIONS.

===== Fire Fighting Measures =====

Flash Point:24F/-4C

Lower Limits:SEE INGRED

Upper

Limits:SEE INGRED

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE AUTO-IGNITE EXPLOS. FOG NOZZLES PREFERRED W/WATER.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT B

E SEEN IMMEDIATELY. OBTAIN MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE SOURCES, CONTAIN SPILL WITH INERT MATERIAL, TRANSFER LIQUID TO COVERED METAL CONTAINERS FOR DISPOSAL. USE ONLY NON-SPARKING TOOLS. PREVENT CONTAMINATION OF S EWERS, STREAMS, & GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F.

STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:EMPTY CONTAINERS SHOULD NOT BE WASHED OR REUSED FOR ANY PURPOSE AND SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DISPOSE AS HAZARDOUS WASTE, IGNITABLE, D001.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN WELL VENTILATED AREAS, RESPIRATORY PROTECTION

MAY NOT BE REQUIRED. IN RESTRICTED AREAS USE A NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. FOR SPRAYING USE MECH PREFILTER. IN CONFINED AREAS USE A NIOSH/ MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:DILUTION & LOCAL EXHAUST VENTILATION RECOMMENDED TO CONTROL CONCENTRATE OF HAZARDOUS INGREDIENTS.

Protective Gloves:WEAR SOLVENT IMPERMEABLE GLOVES.

Eye Protection:SAFETY SPECTACLES WITH SIDE/FACE SHIELD

Work Hygienic Practices:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EA

CH USE & KEEP AWAY FROM CHILDREN.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 302F

Vapor Density:> THAN AIR

Spec Gravity:1.0

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:80

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOUR

CES OF

IGNITION.

Hazardous Decomposition Products:BURNING, HEAT BY WELDING OR CUTTING,  
WILL PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF  
NITROGEN.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND  
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN I/AW FEDERAL, STATE & LOCAL LAWS.

INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED  
CONTAINERS. OBSERVE PRECAUTIO

NS FOR DISP OF FLAMMABLE MATERIALS.

CONTAMINATED ABSOR BENT MAY BE DISPOSED IN A HAZARD WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional adv

ice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.