

EXXON CO USA, A DIV OF EXXON CORP. -- TERESSTIC N150 -- 9150-01-234-7440

===== Product Identification =====

Product ID:TERESSTIC N150
MSDS Date:01/01/1987
FSC:9150
NIIN:01-234-7440
MSDS Number: BJNRY
=== Responsible Party ===
Company Name:EXXON CO USA, A DIV OF EXXON CORP.
Address:800 BELL ST
Box:2180
City:HOUSTON
State:TX
ZIP:77252-2180
Country:US
Info Phone Num:713-656-3424
Emergency Phone Num:7
13-870-6000
CAGE:29700
=== Contractor Identification ===
Company Name:EXXON COMPANY U.S.A.
Box:2180
City:HOUSTON
State:TX
ZIP:77252-2180
Country:US
Phone:713-656-5949 / 713-656-3424
CAGE:29700

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBONS
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC

:NO OSHA:NO

Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. AVOID BREATHING OF MIST.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS LISTED BY THE MANUFACTURER IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES AND SKIN UPON CONTACT.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
First Aid Measures ==
=====

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

=====
Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:480F,249C

Lower Limits:1

Upper Limits:6

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures

:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT, ELIMINATE SOURCES OF IGNITION, AND VENTILATE AREA AS REQUIRED. RECOVER FREE LIQUID.

A

BSORB SMALL SPILL WITH INERT MATERIAL. PLACE WASTE IN DOT APPROVED CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE

=====
Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:AVOID BREATHING OF MIST. MINIMIZE PERIODS OF EXPOSURE TO HIGH TEMPERATURE. AVOID WATER CONTAMINATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:RUBBER GLOVES OR OTHER OIL RESISTANT.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:S

SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE

WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

DISCARD OIL SOAKED SHOES. USE AIR-SUPPLIED RESPIRATORY EQUIPMENT IF EXPOSED TO HOT FUMES.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:755F,402C

Vapor

Pres:0.01

Vapor Density:18

Spec Gravity:0.89

Evaporation Rate & Reference:0.01 NO REFERENCE GIVEN

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT REDDISH LIQUID, VERY SLIGHT HYDROCARBON ODOR

Percent Volatiles by Volume:NEGL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, OR SODIUM OR CALCIUM HYPOCHLORITE.

Stability Condition to Avoid:HIGH TEMP

ERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE, ALDEHYDES AND KETONES, AND OTHER COMBUSTION PRODUCTS OF NITROGEN AND SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Depa

rtment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.