

HULS AMERICA INC -- MIL-L-23699C TURBINE LUBRICANT -- 9150-00-180-6266

=====
Product Identification
=====

Product ID:MIL-L-23699C TURBINE LUBRICANT

MSDS Date:01/18/1989

FSC:9150

NIIN:00-180-6266

MSDS Number: BJPXW

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:80 CENTENNIAL AVE

Box:456

City:PISCATAWAY

State:NJ

ZIP:08855-0456

Country:US

Info Phone Num:201-980-6800

Emergency Phone

Num:201-980-6800/201-763-7173

CAGE:63182

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYOL ESTERS

Other REC Limits:NONE SPECIFIED

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE
PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

=====

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS OR
FUMES FROM EXCESSIVE HEATING MAY CAUSE, RESPIRATORY, EYE AND SKIN
IRRITATION.
Effects of Overexposure:MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE
NAUSEA OR VOMITING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:CONTACT:WASH SKIN WITH SOAP AND WATER. FLUSH EYES WITH WATER
FOR 15 MIN. CALL A PHYSICIAN IF IRRITATION DEVELOPES.
INHALATION:REMOVE VICTIM TO FRESH AIR AND GIVE ARTIFICIAL
RESPIRATION OR OXYGEN IF NE EDED. INGESTION:DO NOT INDUCE
VOMITING.CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:490F,254C
Extinguishing Media:WATER FOG, DRY CHE
MICAL, FOAM OR CARBON DIOXIDE.
Fire Fighting Procedures:BURNING WILL CAUSE TOXIC FUMES. WEAR
SELF-CONTAINED BREATHING APPARATUS AND FULL TURN-OUT GEAR TO FIGHT
FIRE. AVOID SPREADING LIQUID AND FIRE BY WATER FLOODING.
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN
CLOSED CONTAINERS. COOL WITH WATER SPRAY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:COVER WITH AN ENERT ABSORBENT MATERIAL AND
REMOVE TO DISPOSAL
CONTAINER. OBEY ALL RELEVANT FEDERAL, STATE AND
LOCAL LAWS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE ABOVE 490F. WIPE UP SPILLS
IMMEDIATELY. AVOID EYE AND SKIN CONTACT.
Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED
RESPIRATORY PROTECTIVE EQUIPMENT.
Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILAT

ION RECOMMENDED.

Protective Gloves:IMPERMEABLE GLOVES TO MINIMIZE CONTACT.

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:EYE WASH FOUNTAIN. SAFETY SHOWER.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>450F,>232C

Vapor Pres:1

Spec Gravity: