

BAKER SEALANTS & COATINGS CO. -- ADHESIVE -- 8040-00-262-9060

===== Product Identification =====

Product ID:ADHESIVE

MSDS Date:01/01/1987

FSC:8040

NIIN:00-262-9060

MSDS Number: BJPZR

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATINGS CO.

Address:234 SUYDAM AVENUE

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-333-6986

Emergency Phone Num:201-333-6986

CAGE:FO833

==

= Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

===== Compositio

n/Information on Ingredients =====

Ingred Name:PIGMENTS

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

Ingred Name:SOLVENTS

CAS:64742-86-5

RTECS #:LX3296500

Fraction by Wt: 73%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:100 PPM

Ingred Name:OTHER POLYMERS

Fraction by Wt: 27%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:CAN CAUSE IRRITATION TO E
YES, SKIN AND
RESPIRATORY TRACT.

===== First Aid Measures =====

First Aid:SKIN CONTACT: WASH WITH WATER AND SOAP. EYE CONTACT: WASH
WITH WATER AND CALL A PHYSICIAN. EXCESSIVE INHALATION: REMOVE TO
FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:30F/-1C
Lower Limits:1.8
Upper Limits:1.5
Extinguishing Media:FOG, FOAM, DRY CHEMICALS OR CO2
Fire
Fighting Procedures:HANDLE AS VERY FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORBENT CLEANING SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES AND SPARK SOURCES.
PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATORY APPROVED FOR ORGANIC SO

LVENT.
Ventilation:LOCAL EXHAUST AS REQUIRED
Protective Gloves:RUBBER OF POLYETHYLENE.
Eye Protection:GOGGLES TO PREVENT EYE CONTACT.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:132F,56C
Vapor Pres:186
Spec Gravity:.70
Evaporation Rate & Reference:5.0 (BU DSC + 1)
Solubility in Water:INSOLUBLE
Appearance and Odor:BLACK COLORED LIQUID

===== Stability and Reactivity Data =====

Stab
ility Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAMES.

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW FEDERAL & LOCAL APPROVED ENVIRONMENT
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this
information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.