

GLYPTAL, INC -- BLUE RESIN SOLUTION-G7526F -- 8040-00-530-4820

=====
Product Identification
=====

Product ID:BLUE RESIN SOLUTION-G7526F

MSDS Date:05/05/1989

FSC:8040

NIIN:00-530-4820

MSDS Number: BJQCR

=== Responsible Party ===

Company Name:GLYPTAL, INC

Address:305 EASTERN AVE

City:CHELSEA

State:MA

ZIP:02150

Country:US

Info Phone Num:617-884-6918

Emergency Phone Num:617-884-6918

CAGE:FO587

=== Co

Contractor Identification ===

Company Name:GLYPTAL INC

Address:305 EASTERN AVE

Box:NONE

City:CHELSEA

State:MA

ZIP:02150-3344

Country:US

Phone:617-884-6918

CAGE:65313

Company Name:GLYPTAL, INC

Address:305 EASTERN AVE

City:CHELSEA

State:MA

ZIP:02150

Phone:(617) 884-6918

CAGE:FO587

=====
Composition/Information on Ingredients
=====

Ingred Name:VM & P NAPTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 4.7%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:300 PPM

Ingred Name:2-ETHOXYE

THANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000

Fraction by Wt: 4.7%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S,200 PPM

ACGIH TLV:S, 5 PPM; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 58.7%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:STODDARD SOLVENT

CAS:64741-41-9

Fraction by Wt: < 0.1%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:500 PPM

Ingred Name:DIPENTENE

CAS:138-86-3

RTECS #:OS8100000

Fraction by Wt: 0.3%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:200 PPM

Ingred Name:VOC:(LESS WATER): 5.40 LBS/GAL

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:HEADACHE, NAUSEA, DIZZINESS

, CONFUSION AND IRRITABILITY.

Medical Cond Aggravated by Exposure:RESPIRATORY DIFFICULTIES OR PRE-EXISTING SKIN SENSITIZATION

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. ADMINISTER ARTIFICIAL RESPIRATION OR OXYGEN IF BREATHING IS DIFFICULT. SKIN:WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE AND LAUNDRER CONTAMINATED CLOTHING. CONSULT A PHYSICIAN IF IRRITATION PERSISTS. EYES:FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. TAKE TO A PHYSICIAN FOR MEDICAL TREATMENT. INGESTION:CALL A PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:65F/18C

Lower Limits:1.1

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, HOWEVER, WATER MAY BE USED TO COOL CLOSED CONTAINERS THAT ARE EXPOSED TO HEAT. FIREFIGHTING PERSONNEL SHOULD WEAR SCBA.

Unusual Fir

e/Explosion Hazard:PRESS MAY BUILD UP IN CLOSED CONTAINERS THAT ARE EXPOSED TO HEAT.SOLVENT VAPORS ARE HEAVIER THAN AIR & TRAVEL A DISTANCE ALONG GROUND TO IGNIT SOURCE/FLASHBACK.

=====
===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VENT.REMOVE IGNIT SOURCE.ABSORB/DISPOSE USE NON-SPARKING TOOLS.EVACUATE UNPROTECTED PERSONNEL.WATER SPRAY MAY BE USED.TO CONTAIN RUN-OFF,COVER W/ABSORBENT MAT'L & PLACE IN CONTAINER F OR P ROPER DISPOSAL.FLUSH W/WATER TO REMOVE RESIDUE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY PLACE AWAY FROM IGNIT.KEEP CLOSED/UPRIGHT TO PREVENT LEAK.OUTSIDE/DETACHED STORAGE PREFERRED.INSIDE STORAGE SHOULD BE FLAM CABINET.

Other Precautions:METAL CONTAINERS SHOULD BE GROUNDED WHEN TRANSFERRING MATERIAL FROM ONE CONTAINER TO ANOTHER. DO NOT REUSE PRODUCT CONTAINER FOR ANY PURPOSE.

=====
===== Expo

sure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR/OPEN AREA:BUREAU OF MINES APPROVED MECH
FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICULATES OF
OVERSPRAY.INDOORS,WHERE VENTILATION IS INADEQUATE,USE B OF M
APPROVED CHEMICAL-MECHANICAL RES PIRATORS DESIGNED TO REMOVE
PAR/VAPORS.

Protective Gloves:RECOMMENDED IF SKIN CONTACT IS LIKELY.

Eye Protection:CHEMICAL SPLASH GOGGLES RECOMMENDED.

Other Protective Equipment:RECOMMENDED AS NEEDED TO AVOID CON
TACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:250 TO 284F

Vapor Density:> THAN AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIBIBLE

Appearance and Odor:BLUE

Percent Volatiles by Volume:74.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS AND BASES

Hazardous Decomposition Products:BY FIRE: NORMAL PR

ODUCTS OF INCOMPLETE

COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL APPLICABLE
REGULATIONS. DISPOSE OF USING AN APPROVED INCINERATION PROCESS OR
IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS REGARDING
HEALTH AND POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The

United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.