

BAKER SEALANTS & COATINGS CO. -- SOLVENT ADHESIVE -- 8040-00-573-1502

===== Product Identification =====

Product ID:SOLVENT ADHESIVE

MSDS Date:01/01/1987

FSC:8040

NIIN:00-573-1502

MSDS Number: BJQDD

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATINGS CO.

Address:234 SUYDAM AVENUE

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-333-6986

Emergency Phone Num:201-333-69

86

CAGE:FO833

=== Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====

==== Composition/Information on Ingredients =====

Ingred Name:PIGMENTS

Fraction by Wt: 7%

Other REC Limits:NONE SPECIFIED

Ingred Name:VEHICLE

Fraction by Wt: 93%

Other REC Limits:NONE SPECIFIED

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TETRAHYDROFURAN (SARA III)

CAS:109-99-9

RTECS #:LU5950000

Fraction by Wt: 83%

Other REC Lim

its:NONE SPECIFIED

OSHA PEL:200 PPM/250 STEL

ACGIH TLV:200 PPM/250STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== First Aid Measures =====

First Aid:REMOVE VICTIM TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF BREATHING STOPPED.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:6F,-14C

Lower Limits:2

Upper Limits:118

Extinguishing Media:DRY CHEMICAL, CO2

Fire Fighting Procedures:HANDLE AS

VERY FLAMMABLE LIQUID

===== Accidental Release Measures =====

Spill Release Procedures:WEAR RESPIRATORY PROTECTION. FLUSH WITH WATER.
WIPE UP RESIDUE.

===== Handling and Storage =====

Handling and Storage Precautions:VERY FLAMMABLE. PREVENT SKIN CONTACT.
KEEP IN COOL PLACE.

Other Precautions:USE NORMAL GOOD HYGIENE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR PAC OR ORGANIC CANNISTER.

Ventilation:LOCAL EXHAUST AS REQUIRED.

Protective Gloves:NEOPRENE GLOVES

Eye Protection:GOGGLES

Work Hygienic Practices:USE NORMAL GOOD HYGIENE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:147F,64C

Vapor Density:560

Spec Gravity:.97 (ADHESIVE)

Evaporation Rate & Reference:(ETHER =1) 2

Solubility in Water:INSOLUBLE

Appearance and Odor:PUNGENT ODOR, GRAY LIQUID

Percent Volatiles by Volume:90

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS.

Stability Condition to Avoid:SPARKS AND OPEN FLAME. HEAT.

===== Disposal Considerations =====

Waste Disposal Methods:NORMAL WASTE DISPOSAL METHODS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner

er whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.