

KOP-COAT, INC. -- MIL-P-15930C FORMULA 120 GREEN -- 8010-00-664-0018

=====
Product Identification
=====

Product ID:MIL-P-15930C FORMULA 120 GREEN
MSDS Date:11/01/1989
FSC:8010
NIIN:00-664-0018
MSDS Number: BJQDX
=== Responsible Party ===
Company Name:KOP-COAT, INC.
Address:436 SEVENTH AVENUE
City:PITTSBURGH
State:PA
ZIP:15219
Country:US
Info Phone Num:800-547-2468/412-227-2700 OUT OF US
Emergency
Phone Num:800-548-0489/800-424-9300 CHEMTREC
CAGE:HO783
=== Contractor Identification ===
Company Name:KOP-COAT INC
Address:436 7TH AVENUE
City:PITTSBURGH
State:PA
ZIP:15219-1818
Country:US
Phone:800-553-5631, CHEMTREC 800-424-9300
CAGE:00297
Company Name:KOP-COAT, INC.
Address:436 SEVENTH AVENUE
City:PITTSBURGH
State:PA
ZIP:15219
Country:US
Phone:800-547-2468
CAGE:HO783

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-

10-1

RTECS #:SA9275000

Fraction by Wt: 35-40%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 25-30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:TALC

CAS:14807-96-6

RTECS #:VV7720000

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3 TWA

ACGIH TLV:2 MG/M3

Ingred Name:VINYL CHLORIDE (SARA III)

CAS:75-01-4

RTECS #:KU9625000

Fraction by Wt: .1-.2%

Other REC Limits:NONE SPECIFIED

OSHA PEL:SEE 1910.1017

ACGIH TLV:5 PPM, A1; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TRICRESYL PHOSPHATE (EXPOSURE LIMITS ARE TRI-O-CRESYL

PHOSPHATE)

CAS:1330-

78-5
RTECS #:TD0175000
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 MG/M3 TWA
ACGIH TLV:0.1 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INGESTION:MAY CAUSE GASTROINTESTINAL
DISTURBANCES. ASPIRATION INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS
WHICH MAY BE FATAL. INHALE:CHRONIC EXPOSURE TO CERT
AIN CHROMIUM
COMPOUNDS HAS BEEN SHOWN TO INCR EASE LUNG CANCER INCIDENCE.
PROLONGED/REPEATED INHALE OF HIGH CONCENTRATES MAY CAUSE CENTRAL
NERVOUS SYSTEM DEPRESSION
Explanation of Carcinogenicity:SUFF EVIDENCE OF RESPIRATORY
CARCINOGENICITY IN MEN. INCREASED INCIDENCES OF LUNG CANCER AMOUNG
WORKERS. (CHROMIUM VI)
Effects of Overexposure:EYES:MAY CAUSE IRRITATION. SKIN:MAY CAUSE
IRRITATION &/OR DEFATTING,BLISTERING,CRACKING &/OR DRYNESS. CONTACT
W/CHROMATE DUST MAY CAU
SE IRRITATION & POSSIBLE SENSITIZATION.
INHALE:RESPIRATORY IRRITATI
ON,HEADACHE,DIZZINESS,WEAKNESS,NAUSEA,INCOORDINATION & POSSIBLE
COLLAPSE. INGESTION:GASTROINTESTNAL DISTURBANCES.
Medical Cond Aggravated by Exposure:PERSONS W/PRE-EXISTING DISEASE IN
OR A HISTORY OF AILMENTS INVOLVING EYES, SKIN, RESPIRATORY TRACT &
CENTRAL NERVOUS SYSTEM ARE AT GREATER THAN NORMAL RISK OF DEVLOPING
ADVERSE EFFECTS FROM EXPOSURE.

===== First Aid Measures =====
=====

First Aid:EYE:IMMED FLUSH W/LG AMNTS OF WATER 15 MINS,GET MED.SKIN:WASH
THORO W/SOAP & WATER.IF IRRIT OCCURS/PERSISTS,GET MED.WASH CONTAM
CLOTHES BEFORE REUSE.INHALE:REMOVE FROM EXPOSURE.IF BREATH
STOPPED/DIFF, ADMIN CPR/OXYGEN AS NEEDED.GET MED.INGEST:DO NOT
INDUCE VOMIT.GIVE 1 GLASS OF MILK OR 1-2 OZ(30 TO 60G)ACTIVATED
CHARCOAL IN WATER AS TOLERATED.IMMED GET MED.DO NOT GIVE ANYTHING
IF PERSON IS UNCONSC

===== Fire Fighting Measures =====

=====

Flash Point Method:CC

Flash Point:45 F/7.2 C

Extinguishing Media:CO2, DRY CHEMICAL, WATER SPRAY, ALCOHOL OR UNIVERSAL TYPE FOAMS PER MFR'S RECOMMENDATIONS. WATER MAY BE INEFFECTIVE.

Fire Fighting Procedures:WEAR COMPLETE FIRE SERVICE PROTECTIVE EQUIP, INCLUDING FULL-FACE MSHA/NIOSH APPROVED SCBA. USE WATER TO COOL FIRE-EXPOSED CONTAINER/STRUCTURE/PROTECT PERSONNEL

Unusual Fire/Explosion Hazard:VAPOR FORM FLAMM/EXPLOS MIX IN AIR.VAPOR HEAVY,MAY TRAVEL(GROUND /SEWER)TO IGNITE SOURCE-FLASH.FIRE MAY EMIT IRRIT/TOXIC GAS &/OR FUME.CLOSE CONTAIN MAY EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:STOP SPILL IF NO RISK.ELIM ALL IGNITE SOURCES.VENT AREA.AVOID BREATHING VAPOR.AVOID CONTACT W/HOT LIQ/FUMES.TAKE UP CAREFULLY TO AVOID HEAT/SPARKS.USE AN INERT ABSORB TO COMPLETE CLEAN-UP.REPORT RELEA SE INTO ENVIR TO NRC(1-800-424-8802),1 LB OR MORE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREAS/BLDG DESIGN TO COMPLY W/OSHA 1910.106. KEEP IN CLOSED, LABELED CONTAINER W/COOL,WELL SHADED,DRY VENT AREA.PROTECT FROM PHYSICAL DAMAGE

Other Precautions:KEEP CONTAINER CLOSED WHEN MATERIAL IS NOT IN USE.MAINTAIN GOOD HOUSEKEEPING.NOT FOR USE/STORAGE IN/AROUND HOME.GROUND/BOND DRUM.DO NOT USE PRESSURE TO EMPTY DRUMS.KEEP AWAY FROM HEAT & OPEN FLAME.SPR AY PAINT IN ACCORD W/OSHA 29CFR 1910.107

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALE EXPOSURES BELOW PEL(TLV), USE APPROVED UNITS AS PER CURRENT 29CFR1910.134 & NIOSH/RESPIRATOR DECISION LOGIC-PUB. #87.108. IF WITHIN OSHA PROTECTION FACTOR, AIR PURIFYING OV/FILTER UNITS OK.

Ventilation:SUFF GENERAL/LOCAL EXHAUST VENT IN PATTERN/VOL TO CONTROL INHALE EXPOSURE BELOW LIMITS & BELOW FLAMM VAPOR CONCENTRATION

Protective Gloves:INDUSTRIAL RES

INSTANT FLEX TYPE GLOVES

Eye Protection:SAFETY GLASSES/SIDE-FACE SHIELDS/GOGGLES

Other Protective Equipment:WEAR INDUSTRIAL-TYPE WORK CLOTHES & SAFETY FOOTWEAR. PROTECTIVE GARMENTS:HEAD/NECK COVER,APRONS,JACKETS,PAINTS,COVERALLS

Work Hygienic Practices:OBSERVE GOOD HYGIENE & SAFETY PRACTICES WHEN HANDLING THIS PRODUCT. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS.

Supplemental Safety and Health

NOTE TO PHYSICIAN:THERE IS NO SPECIFIC ANTIDOTE FOR EFFECTS FROM OVEREXPOSURE TO THIS MATERIAL. TREATMENT SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS & THE CLINICAL CONDITION.

===== Physical/Chemical Properties =====

Vapor Density:>1

Spec Gravity:8.55 LBS/GAL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN VISCOUS LIQUID WITH TYPICAL SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

HEAT, SPARKS & OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE UPON THERMAL DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. AVOID PROLONG/REPEATED BREATHING OF VAPORS, MIST, FUMES OR SKIN & EYE CONTACT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.