View NSN Online: https://aerobasegroup.com/nsn/2640-00-922-6917

## PEMCO ADHESIVES -- PEMCO ADHESIVE 1599 -- 2640-00-922-6917

============= Product Identification ==============

Product ID:PEMCO ADHESIVE 1599

MSDS Date:12/27/1990

FSC:2640

NIIN:00-922-6917

MSDS Number: BJQGN === Responsible Party ===

Company Name: PEMCO ADHESIVES

Address:1108 AUBURN DR

Box:247

City: AUBURN

State:IN ZIP:46706 Country:US

Info Phone Num:219-925-3368

Emergency Phone Num:800-424-9300, CHEMTREC

**CAGE:PEMC** 

 $\cap$ 

=== Contractor Identification ===

Company Name: ADAMS PSP INC

Address:355 UNIONVILLE RD

Box:City:BUTLER

State:PA ZIP:16003 Country:US CAGE:17705

Company Name: PEMCO ADHESIVES Address: 29542 MANCHESTER DR

City:ELKHART

State:IN

ZIP:46514-5000 Country:US

Phone:219-295-8384

CAGE:PEMCO

======= Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Other REC Limits: NONE SPECIFIED

OSHA PEL:350 PPM/450

STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1 Ingred Name:NITROMETHANE CAS:75-52-5 RTECS #:PA9800000 Other REC Limits: NONE SPECIFIED **OSHA PEL:100 PPM** ACGIH TLV:100 PPM; 9192 ========== Hazards Identification ================ Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: NONE SPECIFIED BY MANUFACTURER. Effects of Overexposu re:DIZZINESS, HEADACHES, NAUSEA, VOMITING. First Aid:INHALATION:MOVE PERSON TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. EYES:FLUSH WITH WATER FOR 15 MIN. SKIN:WASH WITH SOAP AND RUNNING WATER FOR 15 MIN. INGESTION:DO NOT INDUCE VOMITING. SEEK MEDICAL HELP AT ONCE. Flash Point Method:TCC Flash Point:NONE Lower Limits:7.5 Upper Limits:15.0

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

======== Accidental Release Measures ===========

Spill Release Procedures: ABSORB O

============ Handling and Storage ===============
Handling and Storage Precautions:DO NOT STORE IN DIRECT SUNLIGHT. STORE IN COOL DRY AREA. DO NOT STORE IN ALUMINUM CONTAINERS. MAY CAUSE CORROSION. Other Precautions:NONE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:OSHA APPROVED ORGANIC VAPOR MASK. Ventilation:USE ADEQUATE VENTILATION. Protective Gloves:VITON OR NEOPRENE. Eye Protection:GOGGLES Other
Protective Equipment:RUBBER OR PLASTIC APRON WHERE APPROPRIATE. Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE. USE SAFE INDUSTRIAL HYGIENE PRACTICES. Supplemental Safety and Health NONE
========== Physical/Chemical Properties ==========
HCC:N1 Boiling Pt:B.P. Text:165F,74C Vapor Pres:100 @ 20C Vapor Density:4.6 Spec Gravity:1.3 Solubility in Water:NIL Appearance and Odor:BLACK LIQUID WITH SOLVENT ODOR.
======== Stability and Reactivity Data
Stability Indicator/Materials to Avoid:YES STRONG ACIDS AND BASES. Stability Condition to Avoid:EXTREMELY HIGH TEMPERATURES Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES, HYDROGEN CHLORIDE, PHOSGENE.  ==================================
Waste Disposal Methods:CONSULT LOCAL, STATE AND FEDERAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulat

NTO CLAY OR SAWDUST.

ed for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.