

DEXTER ELECTRONIC MTLs DIV.,THE DEXTER CORP. -- HYSOL PC12 007M PART B --
5970-01-099-8525

===== Product Identification =====

Product ID:HYSOL PC12 007M PART B

MSDS Date:11/11/1986

FSC:5970

NIIN:01-099-8525

MSDS Number: BJQHV

=== Responsible Party ===

Company Name:DEXTER ELECTRONIC MTLs DIV.,THE DEXTER CORP.

Address:211 FRANKLIN ST.

City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Info Phone Num:716-

372-6300

Emergency Phone Num:716-372-6309

Preparer's Name:JAMES P HORNBURG

CAGE:04347

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

===== Composition/Information on Ingredients =====

Ingred Name:REACTIVE POLYAMIDE

CAS:37189-83-6

Fraction by Wt: 60-100%

Other REC Limits:NONE SPECIFIED

===== Hazards Ident

ification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN:IRRITATING AND MAY CAUSE
BURNS. PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS.
INHALATION:BREATHING OF VAPORS MAY BE SLIGHTLY IRRITATING.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:IRRITATION OF EYES/SKIN
/RESPIRATORY TRACT.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND
RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.
MATERIAL IS A SENSITIZER AND MAY CAUSE ALLERGIC REACTIONS IN SOME
INDIVIDUALS.

===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.
GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION:
REMOVE TO FRESH AIR. INGESTION: GET MEDI
CAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:338F,170C
Lower Limits:0.6
Upper Limits:2.5
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS
DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:NO SPECIFIC INSTRUCTIONS CITED BY THE
MANUFACTURER.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT
IN USE. PROTECT FROM PHYSICAL DAMAGE.

===== Exposure Controls/Pe

Personal Protection =====

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation: MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE BUT LOCAL SYSTEM IS PREFERABLE.

Protective Gloves: RUBBER GLOVES

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment: SAFETY SHOWER AND EYE BAT

H. INDUSTRIAL TYPE

WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

KEEP CONTAINERS TIGHTLY CLOSED AND AVOID DIRECT EYE AND SKIN CONTACT.

KEY1: THIS IS PART B OF A TWO-PART KIT UNDER THIS NSN.

===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: 634F

, 334C

Vapor Pres: