View NSN Online: https://aerobasegroup.com/nsn/8030-00-285-1568

CHEMICAL COMMODITIES AGENCY, INC. -- RUBBER, SHAFT COV MATL TROWELABLE, PARTA-BASE -- 8030-00-285-1568

============== Product Identification =======================

Product ID:RUBBER, SHAFT COV MATL TROWELABLE, PARTA-BASE

MSDS Date:05/17/1988

FSC:8030

NIIN:00-285-1568

Kit Part:Y

MSDS Number: BJQQY === Responsible Party ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

City:HIGHLAND

State:CA ZIP:92 346

Country:US

Info Phone Num:714-864-2310

Emergency Phone Num:714-864-2310 Preparer's Name:C.A. EISENHARD

CAGE:60777

=== Contractor Identification ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

======= Composition/Information on Ingredients ========

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 34%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV

:50 PPM; 9293

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: VM & P NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000 Fraction by Wt: 9% OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name:LACTOL SPIRITS

CAS:64742-89-8 Fraction by Wt: 9.5% OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name: REFINED NAPHTHENIC OIL

CAS:64742-52-5 RTECS #:PY8035000 Fraction by Wt: 7% OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 20% OSHA PEL:3.5 MG/M3

ACGIH TLV:3 .5 MG/M3; 9192

========== Hazards Identification ================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: MAY BE IRRITANT. SKIN: MAY

CAUSE SKIN IRRITATION AND DERMATITIS UPON PROLONGED OR REPEATED

CONTACT. INHALATION: IT IS A RESPIRATORY TRACT IRRITANT AND ANESTHETIC AND CAUSES CENTRAL NERVOUS SYSTEM DEPRESSION.

INGESTION: MAY CAUSE LIVER AND/OR K

IDNEY DAMAGE.
Medical Cond Aggravated by Exposure:ANY PRE-EXISTING HEART OR SKIN CONDITION OR AN IMPAIRED LUNG FUNCTION.
======================================
First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, BEGIN ARTIF ICIAL RESPIRATION AND CONSULT A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN.
======================================
Flash Point:32.0F,0.0C Lower Limits:1.0 Upper Limits:7.0 Extinguishing Media:FOAM, CARBON DIOXIDE OR DRY CHEMICAL. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.
========= Accidental Release Measures ==========
Spill Release Procedures:ABSORB ON SUITABLE INERT MATERIAL. REMOVE ALL SOURCES OF IGNITION.
============ Handlin g and Storage ====================================
Handling and Storage Precautions:STORE AT 50 F TO 70 F. KEEP AND STORE IN COOL, DRY PLACE AWAY FROM SOURCES OF IGNITION. GROUND DURING TRANSFER.
Other Precautions:REPEATED AND PROLONGED OVEREXPOSURE MAY CAUSE BRAIN AND NERVOUS SYSTEM DAMAGE. CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.
====== Exposure Controls/Personal Protection ========
Respiratory Protection: USE A NIOSH APPROVED CARTRIDGE RESPIRATOR O

R GAS MASK.

Ventilation:MECHANICAL.

Protective Gloves:IMPERMEABLE

Eye Protection: SAFETY GLASSES W/SIDES OR CHEM GOGGLES.

Other Protective Equipment: AVAILABILITY OF EYE WASHES AND SAFETY

SHOWERS IS RECOMMENDED.

Supplemental Safety and Health

======== Physical/Chemical Properties ==========

Boiling Pt:B.P. Text:ABOUT 215 F

Vapor Density:>1 Spec Gravity:1.00

Evaporation Rate & Dr. Reference: