

TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO) -- MIL-H-46170B(2), TYPE II HYD FLUID -- 9150-00-111-6254

===== Product Identification =====

Product ID:MIL-H-46170B(2), TYPE II HYD FLUID

MSDS Date:01/31/1994

FSC:9150

NIIN:00-111-6254

MSDS Number: BJRKS

=== Responsible Party ===

Company Name:TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO)

Address:3365 E SLAUSON AVE

City:VERNON (FORMALLY IN LOS ANGELES)

State:CA

ZIP:90058

Country:US

Info Phone Num:213-581-2036

Emergency Phone Num:213-581-2036, CHEMTREC 800-424-9300

Preparer's Name:RICHARD J. EBERHARDT

CAGE:8Y842

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO

Address:8015 PARAMOUNT BLVD

Box:City:PICO RIVERA

State:CA

ZIP:90660-4811

Country:US

Phone:800-424-9300

CAGE:2X842

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Count

ry:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

Company Name:NAUGHTON ENERGY CORP

Address:RT 940

Box:709

City:POCONO PINES

State:PA

ZIP:18350-0709

Country:US

Phone:570-646-0422

CAGE:1DL10

===== Composition/Information on Ingredients =====

Ingred Name:POLYALPHAOLEFIN BASE STOCK

CAS:68649-12-7

Fraction by Wt: 392F,>200C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG.

Fire Fighting Procedures:DO NOT ENTER CLOSED OR CONFINED AREA W/O

PROPER PROTECTIVE

EQUIPMENT & SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:SLIGHTLY COMBUSTIBLE. WHEN HEATED ABOVE FLASH POINT, WILL RELEASE FLAMMABLE VAPORS WHICH CAN BURN IN OPEN OR EXPLODE IN CONFINED AREA IF EXPOSED TO IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. WIPE OR MOP UP OR ABSORB W/DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN APPROPRIATE CONTAINER FOR DISPOSAL.

Neutralizing Agent:MFR GA  
VE NO INFORMATION ON MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE NEAR OPEN FLAME OR OTHER SOURCES OF IGNITION. EXCESSIVE MISTING MAY CAUSE SLIPPERY FLOORS. PROPER FOOTWARE REQUIRED.

Other Precautions:WASH OR TAKE SHOWER IF GENERAL CONTACT OCCURS. REMOVE OIL SOAKED CLOTHING & LAUNDRER BEFORE REUSE. DISCARD CONTAMINATED LEATHER GLOVES AND SHOES.

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:SUFFICIENT TO MAINTAIN ATMOSPHERE BELOW TLV LIMIT.

Protective Gloves:RECOMMENDED

Eye Protection:REQUIRED

Other Protective Equipment:CHEMICALLY RESISTANT BOOTS & APRONS RECOMMENDED.

Work Hygienic Practices:WASH HANDS W/SOAP & WATER BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

THIS MSDS IS FOR TYPE II MATERIAL (CONTAINING RED DYE) WHILE THE CTDF REQUIRES TYPE I MATERIAL, THAT WITHOUT RED DYE!

==

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:>572F,>300C

Vapor Pres:1

Spec Gravity:0.845

Evaporation Rate & Reference: