

NATIONAL WELDING ALLOYS, INC. -- BAG-1A (S-50); BRAZING ALLOY,SILVER -- 3439-00-262-4186

=====  
Product Identification  
=====

Product ID:BAG-1A (S-50); BRAZING ALLOY,SILVER

MSDS Date:08/01/1990

FSC:3439

NIIN:00-262-4186

MSDS Number: BJRMQ

=== Responsible Party ===

Company Name:NATIONAL WELDING ALLOYS, INC.

Address:1600 SOUTH CANAL STREET

City:PITTSBURGH

State:PA

ZIP:15215

Country:US

Info Phone Num:4

12-781-4255

Emergency Phone Num:412-781-4255

CAGE:0ACE2

=== Contractor Identification ===

Company Name:NATIONAL WELDING ALLOYS INC

Address:1600 SOUTH CANAL STREET

Box:City:PITTSBURGH

State:PA

ZIP:15215-2624

Country:US

Phone:412-781-4255

CAGE:0ACE2

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SILVER (SARA III)

CAS:7440-22-4

RTECS #:VW3500000

Fraction by Wt: 50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.01 MG/M3

ACGIH TLV:0.1 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT

Rpt Qty:1 LB

Ingred Name:COPPER (SARA III)  
CAS:7440-50-8  
RTECS #:GL5325000  
Fraction by Wt: 15.5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.1MG/M3 FUME/1 DUST  
ACGIH TLV:0.2MG/M3 FUME; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC OXIDE  
CAS:1314-13-2  
RTECS #:ZH4810000  
Fraction by Wt: 16.5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15MG/M3 TDUST/5 FUME  
ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:CADMIUM OXIDE (SARA III)  
CAS:1306-19-0  
RTECS #:EV1925000  
Fraction by Wt: 18%  
Other  
REC Limits:NONE SPECIFIED  
OSHA PEL:SEE 1910.1027  
ACGIH TLV:0.05 MG(CD)/M3; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:SHORT TERM EXPOSURE TO WELDING FUMES,  
GASES OR DUST MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA,  
FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES. SKIN  
SENSITIVITY MAY ALSO BE  
NOTED. LONG TERM EXPOSURE TO  
FUMES/GASES/DUST MAY CAUSE PULMONARY IRRITATION OR PNEUMOCONIOSIS.  
Explanation of Carcinogenicity:CADMIUM IS CONSIDERED POSSIBLE  
CARCINOGENS UNDER OSHA AND EPA. RESPIRATORY CANCER FROM WELDING IS  
UNCONFIRMED.  
Effects of Overexposure:EXPOSURE TO WELDING FUMES MAY RESULT IN  
DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR  
IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE  
NOTED. WATERY EYES, HEADACHE, BREATHING DIFFICULT

ULTY, FREQUENT

COUGHING AND/OR CHEST PAINS MAY OCCUR FROM ACUTE EXPOSURE. TOXIC GASES CAN BE FATAL.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH IMPAIRED PULMONARY FUNCTION OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY IRRITANTS CONTAINED IN WELDING FUMES.

=====  
===== First Aid Measures =====

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM EXPOSUR

E AREA AND CALL FOR MEDICAL AID. ADMINISTER OXYGEN IF BREATHING IS D IFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF NO DETECTABLE PULSE, BEGIN EXTERNAL HEART MASSAGE. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:NONCOMBUSTIBLE. USE SUITABLE EXTINGUISHING MEDIA FOR THE NEARBY FIRE.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &

FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATI

ONS. AVOID INHALATION AND SKIN EXPOSU RE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS

LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS.

Ventilation:USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE

Protective Gloves:FLAMEPROOF GAUNTLER GLOVES

Eye Protection:OSHA APPROVED GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment:FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY.

THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THE PRESENCE OF CONTAMINANTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES.

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:1160F,627C

Appearance and Odor:SOLID STRIP

===== Stability and Reactivity Data =====

Stability

Stability Indicator/Materials to Avoid:YES

MINERAL ACIDS, STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:WELDING/CUTTING OPERATIONS MAY INCLUDE ELEMENTAL METALS, OXIDES OF THE METALS, FUMES/GASES & ELECTROMAGNETIC RADIATION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):  
This informati

on is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.