View NSN Online: https://aerobasegroup.kr/nsn/3815-01-291-9223

MOBIL OIL CORP -- MOBIL GREASE 28 -- 9150-01-291-9223

Product ID:MOBIL GREASE 28

MSDS Date:12/08/1989

FSC:9150

NIIN:01-291-9223
MSDS Number: BJSJT
=== Responsible Party ===

Company Name: MOBIL OIL CORP

Address:530 EAST SWEDESFORD ROAD

Box:839

City: VALLEY FORGE

State:PA ZIP:19482 Country:US

Info Phone Num:703-849-3265

Preparer's Name: ENVIRONMENTL AFFAIRS DEPT

CAGE: 1E969

=== Contractor Identification ===
Company Name: MOBIL OIL CORP

Address:530 EAST SWEDESFORD ROAD

Box:1031

City: VALLEY FORGE

State:PA ZIP:19482 Country:US

Phone:703-849-3265

CAGE:1E969

Company Name: SPD TECHNOLOGIES

CAGE:30086

======= Composition/Information on Ingredients ========

Ingred Name:SYNTHETIC OILS

Fraction by Wt: >70%

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: ADDITIVES AND/OR OTHER INGREDIENTS

Fraction by Wt: 5 G/KG(RAT); DERM>2 G/KG(RBT)

R

| Health Hazards Acute and Chronic:NOT EXPECTED TO BE A PROBLEM.  |
|---|
| Explanation of Carcinogenicity:NOT RELEVANT   |
| Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.  Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.  |
| ======================================  |
| First Aid:EYES: FLUSH W/WATER FOR AT LEAST 15 MIN. SKIN: WASH W/SOAP & WATER. HIGH PRESS  |
| ACCIDENTAL INJECT THRU SKIN REQ IMMED ATTN BY MD FOR POSS INCISION, IRRIGATION AND/OR DEBRIDEMENT. INGEST: IF >1/2 LITER (PINT) INGEST, IMMED GIVE 1-2 GLASSES OF WATER & CALL MD, HOSP EMERG RM OR POIS CTL CTR. DO NOT INDUCE VOMIT OR GIVE ANYTHING BY MOUTH TO AN UNCON PERSON. INHAL: NOT EXPECTED TO BE A (SEE SUPP DATA) |
| ======================================  |
| Flash Point Method:COC Flash Point:450F,232C Lower Limits:0.6 Upper Limits:7.0 Extinguis  |
| hing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE. (SEE SUPP DATA) Unusual Fire/Explosion Hazard:NONE  |
| ======== Accidental Release Measures ==========   |
| Spill Release Procedures:SHOVEL UP & DISPOSE OF AT APPROPRIATE WASTE DISPOSAL FACILITY. USCG REGULATIONS REQUIRE IMMEDIATE REPORTING OF SPI   |
| LLS THAT COULD REACH ANY WATERWAY INCLUDING INTERMITTENT DRY CREEKS. (800-424-8802)   |
| Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.  |
| ======================================  |
| Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:NONE SPECIFIED BY MANUFACTURER.  |
| ====== Exposure Controls/Personal Protection ========   |
| Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENT  |
|   |

outes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

ILATION.
Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE

AND WITH ADEQUATE VENTILATION. Protective Gloves: IMPERVIOUS GLOVES

Eye Protection: CHEMICAL WORKERS GOGGLES

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

FIRE FIGHT PROC: IN ENCLOSED AREAS USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. PREVENT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING ST

REAMS OR DRINKING WATER SUPPLY. FIRST AID

PR OC: PROBLEM. IF NECESSARY, REMOVE TO FRESH AIR & SUPPORT BREATHING (GIVE O\*2/ARTIFICIAL RESPIRATION) .

======== Physical/Chemical Properties ==========

Boiling Pt:B.P. Text:>600F,>316C Vapor Pres: