

SIKA CORPORATION -- 433 M100 SIKAFLEX-1A; BLACK -- 2640-00-922-6921

=====
Product Identification
=====

Product ID:433 M100 SIKAFLEX-1A; BLACK

MSDS Date:03/22/1985

FSC:2640

NIIN:00-922-6921

MSDS Number: BJWBP

=== Responsible Party ===

Company Name:SIKA CORPORATION

Address:875 VALLEY BROOK AVENUE

City:LYNDHURST

State:NJ

ZIP:07071

Info Phone Num:(201) 933-8800

Emergency Phone Num:(800) 424-9300

CAGE

:OPMN0

=== Contractor Identification ===

Company Name:ADAMS PSP INC

Address:355 UNIONVILLE RD

Box:City:BUTLER

State:PA

ZIP:16003

Country:US

CAGE:17705

Company Name:SIKA CORPORATION

Address:201 POLITO AVE

Box:City:LYNDHURST

State:NJ

ZIP:07071

Country:US

Phone:201-933-8800

CAGE:0PMN0

Company Name:SIKA CORPORATION

Address:875 VALLEY BROOK AVENUE

City:LYNDHURST

State:NJ

ZIP:07071

Phone:800-424-9300

CAGE:OPMN0

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES

(O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
Other REC Limits:100 PPM
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CALCIUM OXIDE
CAS:1305-78-8
RTECS #:EW3100000
Fraction by Wt: 1%
OSHA PEL:5 MG/M3
ACGIH TLV:2 MG/M3; 9192

Ingred Name:ANATASE (TITANIUM DIOXIDE)
CAS:1317-70-0
RTECS #:BV6550000
Fraction by Wt: 6%
OSHA PEL:15 MG/CUM
ACGIH TLV:15 MG/CUM

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS
#:FF5800000
Fraction by Wt: 2%
Other REC Limits:3.5 MG/CUM (NIOSH)
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

==== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN/EYE: IRRITANT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN/EYE: IRRITANT.
Medical Cond Aggravated by Exposure:PRESENSITIZATION OF PRODUCT

=====

===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. INHALATION: MOVE TO AREA FREE FROM RISK OF FURTHER EXPOSURE. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:143F

Lower Limits:1.0%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:PERSONNEL ENGAGED I

N FIGHTING FIRES MUST BE

PROTECTED AGAINST NITROGEN DIOXIDE FUMES & SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:DURING A FIRE, IRRITATING, TOXIC GASES & AEROSOLS MAY BE PRESENT FROM THE DECOMPOSITION & COMBUSTION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN W/CLOTHING OR ABSORBENT PAPER. IF AREA ENCLOSED, VENTILATE.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE TEMPERATURES BETWEEN 32F-122F. IF CLOSED CONTAINER OF MATERIAL IS EXPOSED TO HEAT, PRESSURE CAN BUILD UP.

Other Precautions:IF MOISTURE ENTERS DRUM, PRESSURE BUILDUP DUE TO REACTION. KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAME. STORE IN TIGHTLY CLOSED CONTAINER/PROTECT FROM MOISTURE & FOREIGN MATERIALS. IDEAL STORAGE TEMPERA TURE IS 50-80F.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

:NONE

Ventilation:LOCAL EXHAUST RECOMMENDED

Protective Gloves:CHEMICALLY RESISTANT RUBBER, PLASTIC

Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES

Other Protective Equipment:AS REQUIRED BY YOUR COMPANY

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume: