

DEFT INC CHEMICAL COATING DIV -- CAT-MIL-C-05285B, ALIPHATIC ISOCYANATE 17925, TYPE I --
8010-01-285-3035

===== Product Identification =====

Product ID:CAT-MIL-C-05285B, ALIPHATIC ISOCYANATE 17925, TYPE I

MSDS Date:06/30/1992

FSC:8010

NIIN:01-285-3035

Kit Part:Y

MSDS Number: BJXBG

=== Responsible Party ===

Company Name:DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:C

A

ZIP:92714-6205

Country:US

Info Phone Num:714-474-0400

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:NORM GAUL

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC POLYISOCYANATE, HEXAMETHYLENE DIISOCYANATE
POLYMER (HDI POLYMER)

CAS:28182-81-2

RTECS #:NQ9170000

Fraction b

y Wt: 45%
Other REC Limits:1 MG/CUM

Ingred Name:HEXAMETHYLENE DIISOCYANATE
CAS:822-06-0
RTECS #:MO1740000
Fraction by Wt: < 0.5%
ACGIH TLV:.005 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:HEXONE, METHYL ISOBUTYL KETONE (MIBK), 4-METHYL-2-PENTANONE
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 25%
Other REC Limits:50 PPM
OSHA PEL:410 MG/CUM
ACGIH TLV:205 MG/CUM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANONE, KETOHEXAMETHYLENE
CAS:108-94-1
RTECS #:GW1050000
Fraction
by Wt: 25%
Other REC Limits:100PPM (SKIN) STEL
OSHA PEL:50 PPM
ACGIH TLV:100 MG/CUM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL 3-ETHOXYPROPIONATE
CAS:763-69-9
RTECS #:UF3325000
Fraction by Wt: 10%

Ingred Name:VOL ORGANIC CMPD: 560 G/L
RTECS #:9999999VO

Ingred Name:WEIGHT PER GALLON IN POUNDS: 8.07 LBS
RTECS #:9999999WG

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:

NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: IRRITATION, DEFATTING, ABSORPTION. INHALATION: RESPIRATORY TRACT/NOSE/THROAT IRRITATION, NERVOUS SYSTEM DEPRESSION. INGESTION: IRRITATION, CORROSIVE TO DIGESTIVE TRACT, ASPIRATION HAZARD. CERTAIN INDIVIDUALS WILL DEVELOP ISOCYANATE SENSITIZATION FROM OVEREXPOSURE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUS

NESS, COMA, DIFFICULTY BREATHING. SKIN:

SWELLING, REDNESS, RASH, CRACKING, DRYNESS. EYES: TEARING, REDNESS, SWEELING, STINGING SENSATION. INGESTION: VOMITING.

Medical Cond Aggravated by Exposure:ASTHMA, OTHER RESPIRATORY DISORDERS, SKIN ALLERGIES, ECZEMA & DERMATITIS.

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NECESSARY.

SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA W/SOAP & WAT

ER. EYES: FLUSH W/CLEAN LUKEWARM WATER FOR 15 MINUTES.

INGESTION: DON'T INDUCE VOMITING. DON'T GIVE FLUIDS TO UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:60F

Lower Limits:1.05%

Upper Limits:9.4%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL & WATER FOG

Fire Fighting Procedures:WEAR SCBA FULL PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAIN

ERS TO PREVENT PRESSURE BUILD

UP/EXPLOSION.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA. REMOVE IGNITION SOURCES.

VENTILATE AREA. CONTAIN & REMOVE W/INERT ABSORBANT & NON-SPARKING TOOLS.

=====
===== Handling and Storage =====

Handling and S

Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY W/OSHA. AVOID HIGH TEMPERATURES, FIRE, OPEN FLAMES, SPARK SOURCES. STORE IN A TIGHTLY CLOSED CONTAINER.

Other Precautions:STORE IN VENTILATED AREA. KEEP CONTAINERS TIGHT/UPRIGHT TO PREVENT LEAKAGE. PREVENT PROLONGED BREATHING OF VAPORS/SPRAY MIST. AVOID CONTACT W/SKIN/EYES. DON'T TAKE INTERNALLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED RESPIRATOR FOR ORGANIC VAPORS,

(AIR/PURIFY/FRESH AIR) VAPOR PARTICULATE RESPIRATOR MAY BE APPROPRIATE WHERE AIR MONITORING DEMONSTRATES VAPOR LEVELS < 10 TIMES THE LIMITS.

Ventilation:EXHAUST TO KEEP AIRBORNE CONCENTRATIONS OF SOLVENT BELOW LIMITS.

Protective Gloves:COTTON, NITROPRENE, RUBBER, POLYETHYLENE

Eye Protection:SAFETY GLASSES W/SIDE SHIELD/FACE SHIELD

Other Protective Equipment:LONG SLEEVE/LEG CLOTHING. GOGGLES.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WA

SH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM.

Supplemental Safety and Health

LIQUID DENSITY: 1

Spec Gravity:0.96879

Evaporation Rate & Reference:(N-BU AC= 1): 0.75

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID W/SOLVENT ODOR

Percent Volatiles by Volume:63.3

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS & SURFACE ACTIVE MATERIALS

Stability Condition

to Avoid:MOISTURE, MATERIAL THAT REACT W/ISOCYANATES & HIGH TEMPERATURES

Hazardous Decomposition Products:CO, CO₂, OXIDES OF NITROGEN & TRACES OF HYDROGEN CYANIDE & HEXAMETHYLENE DIISOCYANIDE

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED W/CARE, DUE TO PRODUCT RESIDUE & FLAMMABLE VAPOR DON'T INCINERATE IN CLOSED CONTAINERS. FLAMMA

BLE LIQUI D UN 1263.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to the
ir
particular situation.