

3M GERERAL OFFICES -- 3M SUPER 74 FOAM FAST, ADHESIVE -- 8040-00-181-7761

=====  
Product Identification  
=====

Product ID:3M SUPER 74 FOAM FAST, ADHESIVE

MSDS Date:03/13/1989

FSC:8040

NIIN:00-181-7761

MSDS Number: BJXHV

=== Responsible Party ===

Company Name:3M GERERAL OFFICES

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-

1110

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====  
Composition/Information on Ingredients  
=====

Ingred

Name: DIMETHYL ETHER  
CAS: 115-10-6  
RTECS #: PM4780000  
Fraction by Wt: 30-40%  
Other REC Limits: 1000 PPM (TWA CMRG)

Ingred Name: PENTANE  
CAS: 109-66-0  
RTECS #: RZ9450000  
Fraction by Wt: 20-30%  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1000 PPM/750 STEL  
ACGIH TLV: 600 PPM/750 STEL; 9293

Ingred Name: NON-VOLATILE COMPONENTS-N.J.(T.S)REGISTRY  
NO.04499600-5490PP(SYNTHETIC  
POLYMER, RESINS, FILLER, ANTIOXIDANT, ROSIN, U.V. ABSOR  
Fraction by Wt: 20-30%  
Other REC Limits: NONE SPECIFIED

Ingred Name: ACETONE (SARA  
III)  
CAS: 67-64-1  
RTECS #: AL3150000  
Fraction by Wt: 10-20%  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 750 PPM/1000 STEL; 9293  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS

Ingred Name: NAPHTHOL SPIRITS \*300 PPM/1900 MG/M3  
CAS: 64475-85-0  
RTECS #: PY8240000  
Fraction by Wt: 1-10%  
Other REC Limits: \*

Ingred Name: VOC: MAXIMUM VOC MINUS WATER MINUS EXEMPT SOLVENTS = 567  
GRAMS/LITER.  
RTECS #: 9999999VO  
Other REC Limits: NONE SPECIFIED

=====  
===== Hazards Identification =====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:MAY CAUSE RESPIRATORY SYSTEM IRRITATION AND TEMPORARY NERVOUS SYSTEM IMPAIRMENT.MAY CAUSE KIDNEY DAMAGE.INTENTIONAL INHALATION OF CONCENTRATED VAPORS IN A CONFINED VESSEL CAN RESULT IN SERIOUS DAMAGE INCLUDING ASPHYXIATION AND DEATH.MAY CAUSE SEVERE DIGESTIVE SYSTEM IRRITATION.

Effects of Overexposure:EYE CONTACT:IRRITATION.SKIN CONTACT:MAY DEFAT SKIN LEADING TO IRRITATION AND DERMATITIS.INHALATION:HEADACHE, DIZZINESS, WEAKNESS, FATIGUE AND UNCONSCIOUSNESS.INGESTION:DIGESTIVE SYSTEM IRRITATION, NAUSEA AND VOMITING. SOLVENT ASPIRATION INTO THE LUNGS AS A RESULT OF VOMITING MAY CAUSE LUNG DAMAGE, WHICH CAN BE FATAL.

===== First Aid Measures =====

First Aid:EYE CONTACT:IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 10 MINUTES. CALL A PHYSICIAN. SKIN:WASH AFFECTED AREA WITH SOAP AND WATER  
. INHALATION:REMOVE PERSON TO FRESH AIR. CALL A PHYSICIAN. SWALLOWED:DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER.

===== Fire Fighting Measures =====

Lower Limits:1.00  
Upper Limits:FLAMM GAS  
Extinguishing Media:CO2, FOAM, DRY CHEMICAL  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING THIS MATERIAL.  
Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE.(TREAT AS FLAMMABLE PRESSURIZED CONTAINER). OVERHEATED, CLOSED CONTAINER ADJACENT TO FIRE COULD EXPLODE DUE TO INTERNAL PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:IF CANS RUPTURE:EXTINGUISH ALL IGNITION SOURCES. VENTILATE AREA.CONTAIN SPILL.COVER WITH ABSORBENT MATERIALS AS NEEDED.COLLECT SPILLED MATERIAL. PLACE IN A U.S. DEPT OF TRANSPORTATION-APPROVED METAL CONTAINER AND SEAL.

===== Handling and Storage =====

ge =====

Handling and Storage Precautions:FOR INDUSTRIAL/PROFESS USE ONLY.KEEP AWAY FROM HEAT,SPARK,FLAME/OTHER SOURCES OF IGNIT.AVOID BREATHING VAPOR AND MIST.DO NOT STORE AT TEMPS ABOVE 120F

Other Precautions:THE VAPORS RELEASED BY THIS PRODUCT CAN EASILY BE IGNITED AND BURN EXPLOSIVELY.PREVENT SKIN/EYE CONTACT.DO NOT TAKE INTERNALLY.USE ONLY AS DIRECTED.DO NOT PUNCTURE OR INCINERATE CONTAINER.KEEP OUT OF THE REACH OF CHILDREN.

===== Exposure C  
ontrols/Personal Protection =====

Ventilation:LOCAL EXHAUST IF LARGE AMNTS ARE SPRAYED IN SHORT PERIOD OF TIME.USE ONLY W/VENT SUFF TO MAINTAIN VAPOR CONC BELOW LIMIT

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:WEAR CHEMICAL SAFETY GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:>2.00

Spec Gravity: