View NSN Online: https://aerobasegroup.kr/nsn/5330-00-618-3221

AMERICAN BRAIDING AND MFG CORP -- 340, 340BIL -- 5330-00-618-3221

Product ID:340, 340BIL MSDS Date:01/01/1991

FSC:5330

NIIN:00-618-3221

MSDS Number: BJXMZ === Responsible Party ===

Company Name: AMERICAN BRAIDING AND MFG CORP

Address:RT 79 AND BEACON HILL RD

Box:397

City:MORGANVILLE

State:NJ ZIP:07751 Country:US

Info Phone Num:201-591-0725 Emergency Phone Num:201-

591-0725 CAGE:4R345

=== Contractor Identification ===

Company Name: AMERICAN BRAIDING AND MFG CORP

Address:247 OLD TAVERN ROAD

Box:City:HOWELL

State:NJ ZIP:07731 Country:US

Phone:732-938-6333 ...FAX 6377

CAGE:4R345

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS, CHRYSOTILE

CAS:12001-29-5 RTECS #:CI6478500

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC,A1; 9495

Ingred Name: TEFLON (TETRAFLUORO ETHYLENE POLYMER)

CAS:116-

Other REC Limits: NONE SPECIFIED Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Health Hazards Acute and Chronic: EXPOSURE TO PTFE FUMES ABOVE 500F CAN CAUSE TEMPORARY FLU LIKE SYMPTOMS. Explanation of Carcinogenicity:NTP:KNOWN TO BE CARCINOGENIC. IARC: SUFFICIENT EVIDENCE THAT THE AGENT IS CARCINOGENIC TO HUMANS. OSHA:CARCINOGEN Effects of Overexposure: NONE IMMEDIATE. LONG TERM EXPOSURE TO ASBESTOS CAN CAUSE MESOTHELIOMA (A LUNG DISEASE). Medical Cond Aggravated by Exposure: RESPIRATORY DISEASE. NONE SPECIFIED BY MANUFACTURER. First Aid: NONE SPECIFIED BY MANUFACTURER. Flash Point: NON-FLAMMABLE Extinguishing Media: SOME OIL MAY SEEP FROM THIS MATERIAL SO USE THE **APPROPRI** ATE EXTINGUISHING MATERIAL. Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE ========= Accidental Release Measures ============ Spill Release Procedures: NORMAL CLEANUP. Neutralizing Agent:NONE ============ Handling and Storage =========================== Handling and Storage Precautions: NONE Other Precautions: AVOID CREATING DUST AND FUMES. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: SELECT APPROPRIATE RES

14-3

RTECS #:KX4025000

TABLE I OF 1910.1001 BASED ON EMPLOYEE EXPOSURE. Ventilation:NONE Protective Gloves:NONE Eye Protection:NONE
Other Protective Equipment:NONE Work Hygienic Practices:AVOID CREATING DUST AND FUMES. Supplemental Safety and Health NONE
========= Physical/Chemical Properties =========
HCC:T6 Spec Gravity:1.5 Solubility in Water:INSOLUBLE Appearance and Odor:WHITE TO GRAYISH SHINY ROPE.
======================================
Stability Indicator/Materials to Avoid:YES STRONG ACIDS AND ALKALIES. Stability Condition to Avoid:AVOID TEMPERATURES EXCEEDING 600F. Hazardous Decomposition Products:TETRAFLUOROETHYLENE FROM 800F, HEXAFLUOROPROPYLENE FROM 850F AND CARBONYL FLUORIDE FROM 930F
====== Disposal Considerations =========
Waste Disposal Methods: AS REQUIRED BY STATE, FEDERAL AND LOCAL AGENCIES.

Disclaimer (provided with this information by the compiling agencies): This info

PIRATORY PROTECTION FROM

rmation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.