

MOBIL OIL CORP -- MOBIL DTE OIL LIGHT -- 9150-01-043-9063

===== Product Identification =====

Product ID:MOBIL DTE OIL LIGHT

MSDS Date:04/14/1989

FSC:9150

NIIN:01-043-9063

MSDS Number: BJXQP

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:150 E 42ND ST

City:NEW YORK

State:NY

ZIP:10017-5612

Country:US

Info Phone Num:703-849-3265 OR 800-662-4525

Emergency Phone Num:212-883-4411

CAGE:1E

969

=== Contractor Identification ===

Company Name:CONVOY OIL CORP

Address:1410 N FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA

ZIP:19125

Country:US

Phone:215-739-5281

CAGE:6A438

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

Company Name:MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV.

Address:RT 27 AND VINEYARD RD.

Box:250

City:EDISON

State:NJ

ZIP:08818-0250

Country:US

Phone:609-737-4411 OR 800

-424-9300  
CAGE:77988  
Company Name:MOBIL OIL CORP  
Address:530 EAST SWEDES FORD ROAD  
Box:1031  
City:VALLEY FORGE  
State:PA  
ZIP:19482  
Country:US  
Phone:703-849-3265  
CAGE:1E969

=====  
Composition/Information on Ingredients  
=====

Ingred Name:REFINED MINERAL OIL  
Fraction by Wt: >95%  
Other REC Limits:NONE SPECIFIED

Ingred Name:ADDITIVES AND OTHER INGREDIENTS  
Fraction by Wt: 15 G/KG (ESTIMATED)  
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC  
:NO OSHA:NO

Health Hazards Acute and Chronic:ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO OIL MIST POSES A RISK OF PULMONARY DISEASE SUCH AS CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY LEAD TO CHEMICAL PNEUMONITIS.

Explanation of Carcinogenicity:IARC HAS DETERMINED THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY IN EXPERIMENTAL ANIMALS OF USED MOTOR OIL.

Effects of Overexposure:GENERALLY CONSIDERED MINIMALLY IRRITATING TO THE EYES AND MILDLY IRRITATING TO THE SKIN. PROLONGED AND REPEATED CONTACT MAY RESULT IN VARIOUS SKIN DISORDERS SUCH AS DERMATITIS, FOLLICULITIS OR OIL AC NE. INHALATION OF VAPOR OR OIL MIST MAY CAUSE MILD UPPER RESPIRATORY TRACT IRRITATION. SLIGHTLY TOXIC IF SWALLOWED.

Medical Cond Aggravated by Exposure:PREEXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED

BY EXPOSURE TO THIS PRODUCT.

=====  
===== First Aid Measures =====  
=====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: MAY ACT AS A LAXATIVE. DO NOT INDUCE VOMITING. RELATIVELY NON  
-TOXIC UNLESS  
ASPIRATED.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:COC  
Flash Point:425F,218C  
Lower Limits:0.6  
Upper Limits:7.0  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.  
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATERCOURSES, REMOVE ALL SOURCES OF IGNITION. ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS, ETC.

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS. COMBUSTIBLE LIQUID.  
Other Precautions:MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES THAT CAN NOT BE DECONTAMINATED.

=====  
===== Exposure Controls/Personal Protection  
=====

=====

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES OR AN ATMOSPHERE-SUPPLYING RESPIRATOR IF REQUIRED. PROTECTION IS NOT REQUIRED UNDER NORMAL USE CONDITIONS.

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE. MECHANICAL EXHAUST RECOMMENDED IF USED IN ENCLOSED AREA.

Protective Gloves:CHEMICAL RESISTANT GLOVES (NITRILE BEST)

Eye Protection:WEAR CHEMICAL SAFETY GOGGLES

Other Protective Equip

ment:WEAR PROTECTIVE CLOTHING, APRON AND BOOTS AS REQUIRED TO MINIMIZE SKIN CONTACT.

Work Hygienic Practices:MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DIRNKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

THIS PRODUCT IS CLASSIFIED AS AN OIL UNDER SECTION 311 OF THE CLEAN WATER ACT. SPILLS ENTERING SURFACE WATERS OR ANY WATER COURSES OR SEWERS ENTERING/LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER. 800-424-8602

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: