View NSN Online: https://aerobasegroup.kr/nsn/8040-01-152-8105

DEXTER ADHESIVES AND STRUCTURAL MATERIALS -- EA9309 NA PART B -- 8040-01-152-8105

Product ID: EA9309 NA PART B MSDS Date:09/29/1989 FSC:8040 NIIN:01-152-8105 Kit Part:Y MSDS Number: BJYCB === Responsible Party === Company Name: DEXTER ADHESIVES AND STRUCTURAL MATERIALS Address:2850 WILLOW PASS ROAD Box:312 City:PITTSBURG State:CA ZIP:94565 Country:US Info Phone Num :415-687-4201 Emergency Phone Num:800-424-9300 (CHEMTREC) CAGE:33564 === Contractor Identification === **Company Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS** Address:2850 WILLOW PASS ROAD Box:312 **City:BAY POINT** State:CA ZIP:94565-3299 Country:US Phone:202-483-7616 CAGE:33564

Ingred Name: ALKYLAMINES

Ingred Name:VOC 300F,>149C Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, WATER SPRAY, FOAM OR FOG. Fire F ighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS. Unusual Fire/Explosion Hazard: DENSE SMOKE AND TOXIC GASES MAY BE LIBERATED. Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS. OBSERVING SOLVENT FLAMMABILITY CAUTIONS. ======================== Handling a Handling and Storage Precautions: KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG. F) FOR 12 MONTHS. Other Precautions: FOLLOW RECOMMENDED CURING SCHEDULE. USE ONLY IN WELL VENTILATED AREAS. Respiratory Protection: NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION. Ventilation:LOCAL EXHAUST RECOMMENDED. Protective Gloves: IMPERVIOUS PLASTIC OR RUBBER. Eye Pro tection:SAFETY GLASSES OR GOGGLES. Other Protective Equipment: AS NEEDED TO PROTECT SKIN AND CLOTHING. Supplemental Safety and Health AVOID MIXING RESIN AND CURING AGENT IN BATCHES GREATER THAN 1 POUND TOTAL. DO NOT HEAT MIXED ADHESIVE UNLESS CURING SURFACES TO BE

TOTAL. DO NOT HEAT MIXED ADHESIVE UNLESS CURING SURFACES TO BE BONDED. FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD -UP W/RELEASE OF TOXIC GASES. PART B CONTAINS ALKYLAMINES. DO NOT HANDLE OR USE UNTIL MSDS HAS BEEN READ & UNDERSTOOD.

Vapor Density:8.45 Spec Gravity:1.02 Evaporation Rate & amp; Reference:NIL Appearance and Odor:REDDISH-ORANGE LIQUID WITH AMMONIACAL ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS. Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.

Waste Disposal Methods: DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profession al advice to verify and assume responsibility for the suitability of this information to their

particular situation.