View NSN Online: https://aerobasegroup.kr/nsn/3439-00-273-3722

FEDERATED-FRY METALS -- ROSIN FLUX CORED SOLDER WIRE WRAP -- 3439-00-273-3722

Product ID:ROSIN FLUX CORED SOLDER WIRE WRAP

MSDS Date:07/18/1989

FSC:3439

NIIN:00-273-3722

MSDS Number: BJYGS === Responsible Party ===

Company Name: FEDERATED-FRY METALS Address: 6TH AVENUE AND 41ST STREET

City:ALTOONA

State:PA ZIP:16602 Country:US

Info Phone Num:814-946-1611

Emergency

Phone Num:814-946-1611/800-424-9300(CHEMTREC)

CAGE:0C2W5

=== Contractor Identification ===

Company Name: FEDERATED-FRY METALS Address: 6TH AVENUE AND 41ST STREET

Box:City:ALTOONA

State:PA ZIP:16602 Country:US

Phone:814-946-1611/800-424-9300(CHEMTREC)

CAGE:0C2W5

====== Composition/Information on Ingredients ========

Ingred Name:TIN CAS:7440-31-5 RTECS #:XP7320000

KTLOS #.XF / 320000

Other REC Limits: NONE SPECIFIED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTEC

S #:OF7525000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB

Ingred Name:SILVER (SARA III)

CAS:7440-22-4

DOT Rpt Qty:1 LB

RTECS #:VW3500000

Other REC Limits: NONE SPECIFIED

OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH

CAS:7440-69-9

RTECS #:EB2600000

Other REC Limits: NONE SPECIFIED

Ingred Name:INDIUM

CAS:7440-74-6

RTECS #:NL1050000

Other REC Limits: NONE SPECIFIED

OSHA PEL:0.1 M

G/M3

ACGIH TLV:0.1 MG/M3; 9192

Ingred Name: ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000

Other REC Limits: NONE SPECIFIED

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG SB/M3; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ROSIN ACID

CAS:8050-09-7 Fraction by Wt: 1-4%

Other REC Limits: NONE SPECIFIED

=========== Hazards Identification ===============

LD50 LC50 Mixture:LD50 ORAL RAT > 5000 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcin

ogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:HEALTH HAZARDS: ACUTE: EYE AND SKIN IRRITATION AND BURNS, RESPIRATORY TRACT IRRITATION. CHRONIC: KIDNEY AND CENTRAL NERVOUS SYSTEM EFFECTS DUE TO LEAD. NASAL ULCERATION AND STOMACH IRRITATION DUE TO A NTIMONY.

Explanation of Carcinogenicity: LEAD IS LISTED UNDER NTP AND IARC.

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, BURNS.

INHALATION: RESPIRATORY TRACT IRRITATION, DIZZINESS, HEADACHE DUE

TO ROSIN. INGESTION: ANEMIA, INSOMNIA, WEAKNESS, IRRITABILITY, CONSTIPATION, STOMACH, PAINS DUE TO LEAD. FEVER, NAUSEA, STOMACH CRAMPS, DIARRHEA DUE TO TIN. STOMACH AND NASAL IRRITATION DUE TO ANTIMONY.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING KIDNEY OR CENTRAL NERVOUS SYSTEM DISORDERS MAY BE MORE AT RISK FROM EXPOSURE.

First Aid:EYES: FOR FUME IRRITATION, REMOVE FROM EXPOSURE. IF

IRRITATION PERSISTS, SEE DOCTOR. SKIN: FOR BURNS, COOL WITH COLD WATER AND GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS D IFFICULT, ADMINISTER OXYGEN AND GET MEDICAL ATTENTION. INGESTION: GET MEDICAL HELP IMMEDIATELY.

========= Fire Fighting Measures ============

Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A

FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS SUCH AS TOXIC LEAD FUMES.

	Accidental	Release	Measures	
--	------------	---------	----------	--

Spill Release Procedures:IF MOLTEN, ALLOW TO COOL AND SOLIDIFY. THEN SCRAPE UP AND PLACE IN APPROPIATE DISPOSAL CONTAINER.

====== Handling and

Handling and Storage Precautions:NO SPECIAL REQUIREMENTS. Other Precautions:NONE SPECIFIED BY MANUFACTURER.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:FUME RESPIRATOR FOR ORGANIC VAPORS OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV. Ventilation:LOCAL EXHAUST TO KEEP BELOW TLV. Protective Gloves:PROTECTIVE GLOVES. Eye Protection:FACESHIELD OR GOGGLES. Ot
her Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKING, APPLYING COSMETICS OR USING SANITARY FACILITIES. Supplemental Safety and Health
NO FOOD, DRINKING OR TOBACCO SHOULD BE ALLOWED WHERE CORE SOLDER IS USED.
========= Physical/Chemical Properties ==========
HCC:N1 Solubility in Water:NIL Appearance and Odor:SILVER GREY WIRE.
======== Stability and Reactivity Data =========
St ability Indicator/Materials to Avoid:YES OXIDIZERS, STRONG ACIDS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:FORMALDEHYDE, CARBON MONOXIDE, ROSIN AND ROSIN DERIVATIVES.
======= Disposal Considerations ==========
Waste Disposal Methods:CONSULT WITH YOUR LOCAL ENVIRONMENTAL OFFICER. MANUFACTURER RECOMMENDS TO RETURN FOR REPROCESSING. DISPOSE OF

Storage ==========

IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATI

ONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular s ituation.