

HASKON CORPORATION AIRCRAFT PRODUCT SALES -- DIALATOR-12501 -- 6850-00-224-6656
===== Product Identification =====

Product ID:DIALATOR-12501
MSDS Date:01/19/1978
FSC:6850
NIIN:00-224-6656
MSDS Number: BJYSY
=== Responsible Party ===
Company Name:HASKON CORPORATION AIRCRAFT PRODUCT SALES
Address:336 WAIR ST
City:TAUNTON
State:MA
ZIP:02780-4234
Country:US
Info Phone Num:508-824-4011
Emergency Phone
Num:508-824-4011
CAGE:11960
=== Contractor Identification ===
Company Name:HASKON CORPORATION AIRCRAFT PRODUCT SALES
Address:336 WAIR ST
Box:City:TAUNTON
State:MA
ZIP:02780-4234
Country:US
Phone:508-824-4011
CAGE:11960

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 13.8%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA R

pt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 43.2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 43.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-EYE/SKIN:MILD
IRRITATION.INHALATION:ANESTHESIA,HEADACHE,NAUSEA,DIZZINESS.CHRONIC-
NOT GIVEN.
Effects of Overexposure:SEE HEALTH HAZARDS SECTION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
==== First Aid Measures =====

First A
id:GET MEDICAL ATTENTION-EYE:FLUSH W/WATER 15 MIN,HOLD LIDS
OPEN.SKIN:FLUSH WITH WATER.INHALED:REMOVE TO FRESH AIR.IF
SWALLOWED:CALL A DOCTOR.

=====
==== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:22.0F,-5.6C
Autoignition Temp:Autoignition Temp Text:960F
Lower Limits:1.8
Upper Limits:10.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A

FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:NONE NOTED; COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ANY FLAMES & SHUT OFF LEAK IF WITHOUT RISK.WEAR PROTECTIVE EQUIPMENTS.ABSORB SMALL SPILL ON PAPER,VERMICULITE.LARGE SPILLS:DIKE AREA.PUMP LIQUID TO SALVAGE TANK.TAKE UP THE REST BY SAND/CLAY & SHOVEL TO A CONTAINER.PUMP SHOULD NOT GET TOO HOT.

Neutralizing Agent:NONE GIVEN

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS TIGHTLY CLOSED IN A COOL,WELL VENTILATED PLACE,AWAY FROM HEAT & FLAMES.EMPTY CONTAINER MAY CONTAIN HAZARDOUS RESIDUES.

Other Precautions:OBSERVE ALL LABELED HAZARD PRECAUTIONS.CLOSURES SHOULD BE REMOVED CAREFULLY TO RELIEVE POSSIBLE INTERNAL PRESSURE AND,WHEN EMPTY,TO AVOID ACCIDENTAL EXPOSURE TO ANY ENTRAPPED VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKPLACE EXPOSURE LIMIT OF PRODUCT EXCEEDS THE TLV, A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR A SELF-CONTAINED BREATHING APPARATUS IS ADVISED.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION.

Protective Gloves:PVA

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective E

quipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:DO NOT INHALE VAPORS. WASH HANDS BEFORE EATING AND DRINKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=79.4C, 175.F

Vapor Pres:70

Vapor Density:2.9

Spec Gravity:0.868

Evaporation Rate & Reference:2.0 (N-BUTYL ACETATE=1)

Solubility in Water:MODERATE

Appearance and Odor:COLORLESS LIQUID-A

ROMATIC

Percent Volatiles by Volume:100.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE NOTED

Stability Condition to Avoid:HIGH HEAT

Hazardous Decomposition Products:CARBON MONOXIDE AND DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT FEDERAL, STATE AND LOCAL AUTHORITIES FOR
PROPER DISPOSAL PROCEDURES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.