

PRATT AND LAMBERT INC -- LAC ACRYLIC N/C CAM BLACK 37038 ID 792702 -- 8010-00-527-2884  
===== Product Identification =====

Product ID:LAC ACRYLIC N/C CAM BLACK 37038 ID 792702  
MSDS Date:02/14/1991  
FSC:8010  
NIIN:00-527-2884  
MSDS Number: BJYYH  
=== Responsible Party ===  
Company Name:PRATT AND LAMBERT INC  
Address:16116 E 13TH ST  
Box:2153  
City:WICHITA  
State:KS  
ZIP:67201  
Country:US  
Info Phone Num:316-73  
3-1361  
Emergency Phone Num:716-873-6000 DOT EMER 8002553924  
CAGE:61196  
=== Contractor Identification ===  
Company Name:PRATT AND LAMBERT INC  
Box:6027  
City:CLEVELAND  
State:OH  
ZIP:44101-1027  
Country:US  
Phone:216-566-2902  
CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SARA III)  
CAS:110-19-0  
RTECS #:AI4025000  
Fraction by Wt: 45%  
Other REC Limits:LFL:2.0/UFL:11.0  
OSHA PEL:150 PPM  
ACGIH TLV:150 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:

5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: < 5%

Other REC Limits:LFL:3.0/UFL:13.0

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE

CAS:9004-70-0

RTECS #:WG2934500

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, AMORPHOUS HYDRATED

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7

RTECS #:TI0350000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3/10 STEL

ACGIH TLV:5

MG/M3; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 10%  
Other REC Limits:LFL:1.7/UFL:7.1  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 5%  
Other REC Limits:LFL:2.0/UFL:10.0  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300 STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:50  
00 LBS

Ingred Name:VOC. 5.33 LB/GAL LESS WATER & NPRS\* 640 G/L LESS WATER  
CALCULATED  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC. 20.95 LB/GAL SOLIDS 2514 G/L SOLIDS CALCULATED  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:OVEREXPOSURE TO TOLUENE CAUSE  
LIVER

DAMAGE. SYNERGISTIC EFFECT HAS RESULTED IN PERIPHERAL NEUROPATHY IN  
HUMANS OVEREXPOSURE TO SOLVENTS CAUSE PERMANENT BRAIN AND NERVOUS  
SYSTEM DAMAGE. INTENTIONAL MIS USE BY DELIBERATELY CONCENTRATING  
AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:DI(2-ETHYLEHEXYL) PHTHALATE IS LISTED AS  
A POTENTIAL CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM.

Effects of Overexposure:SWALLOWING:GASTROINTESTINAL IRRIT,NAUSEA,  
VOMIT.ASPIRATION OF MA

TERIAL INTO THE LUNGS MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: NOSE, THROAT IRRIT, ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHES, DIZZINESS, NAUSEA & CONFUSION. EYE: SEVERE IRRIT & CORNEAL DAMAGE. SKIN: MAY CAUSE DEFATTING AND IRRITATION.

=====  
===== First Aid Measures =====  
=====

First Aid: SWALLOWED: DO NOT INDUCE VOMIT. CALL POISON CNTRL CNTR/DOCTOR IMMEDIATELY. INHALED: REMOVE TO FRESH AIR IMMEDIATELY. IF BREATHING STOP, GIVE ART RESPIRATION. KEEP WARM/QUIET. GET MED ATTENTION IMMEDIATELY. EYES: FLUSH WITH LOTS OF WATER, LIFT UPPER/LOWER LIDS FOR 15 MIN. GET MED ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHES. WASH AREA WITH SOAP/WATER. GET MED ATTENTION IF IRRITATION PERSISTS. ANY TREATMENT FOR OVEREXPOSURE SHOULD BE DIRECTED AT CONTROL OF SYMPTOMS/CLINICAL CONDITION.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point: 24F/-4C  
Lower Limits: 1.7  
Upper Limits: 13.0  
Extinguishing Media: NFPA CLASS B FIRE EXTINGUISHERS (CO2, ALL PURPOSE DRY CHEM, ALCOHOL FOAM) FOR EXTENDING FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.  
Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP/POSSIBLE AUTO-IGNITION/EXPLOSION WHEN EXPOSED TO HIGH HEAT. IF WATER USED, FOG NOZZLES.  
Unusual Fire/Explosion Hazard: DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures: KEEP SPEC AWAY. ELIMINATE IGNITION SOURCES. DIKE/CONTAIN WITH INERT MATERIAL. MOVE LIQUID TO COVERED METAL CONTAINER FOR RECOVERY/DISPOSAL/REMOVE WITH INERT ABSORBENT. USE NON-SPARKING TOOL. PLACE ABSORBENT DIKE MATERIAL IN COVERED METAL CONTAINER FOR DISPOSAL, PREVENT CONTAMINATION OF SEWER.

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions: DO NOT STORE ABOVE 100F(38C). STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.1

06.CLOSE

CONTAINER AFTER EACH USE.DO NOT BREATHE SANDING DUST.

Other Precautions:DO NOT TAKE INTERN.KEEP AWAY FROM CHILDREN.DO NOT WASH/ REUSE EMPTY CONTAINERS FOR ANY PURPOSE.CONTAINERS SHOULD BE GROUND/BOND TO RECEIVING CONTAINER.DO NOT WELD,BRAZE/CUT EMPTY CONTAINER.NEVER USE P PRESS TO EMPTY.DR IS NOT A PRESS VESSEL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED VENT AREAS A CHEM CARTRIDGE RSPRTR MAY BE REQUIRED.

UNDER CERTAIN CONDITIONS,A MECHANICAL PREFILTER MAY ALSO BE REQUIRED.IN CONFINED AREAS USE AN AIR SUPPLIED RSPRTR.IF TLV'S EXCEEDED USE RESPIRATOR WITH APPROP PROTEC FACTOR

Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME/PATT TO MAINTAIN CONC BELOW EXPOS LIMITS.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES ARE REQUIRED.

Eye Protection:SAFETY GLASSES W/SIDESHIELDS/FACESHIELD.

Supplemental Safety and Health

=====  
===== Physical/Chemical

Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 288F

Vapor Density:> AIR

Spec Gravity:1.0

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Appearance and Odor:PAINT

Percent Volatiles by Volume:74

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>100F(38C)) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:B  
URNING, INCLUDING WHEN HEATED BY  
WELDING OR CUTTING, WILL PRODUCE SMOKE, CO AND CO2. IN ADDITION,  
OXIDES OF NITROGEN.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD WITH FED,STATE & LOCAL LAWS.  
INCINERATE ONLY IN EPA PERMITTED FACILITY.DO NOT BURN CLOSED  
CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMM  
MAT'L.CONTAMIN ABSORB MAY BE DISPOSED IN A HAZARDOUS WASTE  
LANDFILL.HAZARDOUSWASTE D000

Disclaimer (

provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.