

DRACKETT PRODUCTS COMPANY -- INSTITUTION FORM WINDEX GLASS CLEANER PROF. --  
7930-00-963-4068

=====  
===== Product Identification =====

Product ID:INSTITUTION FORM WINDEX GLASS CLEANER PROF.

MSDS Date:01/06/1989

FSC:7930

NIIN:00-963-4068

MSDS Number: BJZGW

=== Responsible Party ===

Company Name:DRACKETT PRODUCTS COMPANY

Address:5020 SPRING GROVE AVE

City:CINCINNATI

State:OH

ZIP:45232-1988

Country:US

Info

Phone Num:513-632-1500

Emergency Phone Num:513-632-1500

CAGE:DRACK

=== Contractor Identification ===

Company Name:DRACKETT CO

Address:5020 SPRING GROVE AVE

Box:City:CINCINNATI

State:OH

ZIP:45232-1926

Country:US

Phone:513-632-7409

CAGE:85234

Company Name:DRACKETT PRODUCTS CO

Address:5020 SPRING GROVE AVE

City:CINCINNATI

State:OH

ZIP:45232-1988

Country:US

Phone:513-632-1500

CAGE:DRACK

=====  
===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

C

AS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: < 4%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:2-BUTOXYETHANOL  
CAS:111-76-2  
RTECS #:KJ8575000  
Fraction by Wt: < 3%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:S, 50 PPM  
ACGIH TLV:S, 25 PPM; 9293

===== Hazards Identification =====

Effects of Overexposure:EYE CONTACT:SENSATION OF IRRITATION.

===== First Aid Measures =====

First Aid:THIS PRODUCT IS NOT AN EYE OR SKIN IRRITANT OR TOXIC IF  
INGESTED SO AS TO REQUIRE FIRST AID PROCEDURES ON THE PRODUCT LABEL  
UNDER CONSUMER PRODUCT SAFETY COMMISSION RULES. HOWEVER, THE  
FOLLOWING STEPS MAY BE TAKEN TO LESSEN DISCOMFORT: EYES AND  
SKIN:FLUSH EYES OR SKIN WITH WATER. IF INGESTED: DRINK MILK OR  
WATER FREELY.

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:129F/54C  
Extinguishing Media:IF INVOLVED  
IN FIRE, USE WATER, DRY ALCOHOL-TYPE/ALL  
PURPOSE FOAM, DRY CHEMICAL, CO2 OR OTHER CLASS B EXTINGUISHING AGENTS  
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING PRESSURE  
DEMAND SCBA AND TURNOUT EQUIPMENT SHOULD BE WORN BY FIREFIGHTERS  
AND OTHERS EXPOSED TO COMBUSTION BY-PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:IN CASE OF SPILL OR LEAK FLUSH AREA WITH  
WATER. KEEP OUT OF WATERSHED AND WATER SYSTEMS.

=====

===== **Handling and Storage**=====

Other Precautions:UNPLUG ELECTRICAL APPLIANCES BEFORE USING PRODUCT ON THEM.

===== **Exposure Controls/Personal Protection**=====

Supplemental Safety and Health

===== **Physical/Chemical Properties**=====

HCC:F4

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:17.7

Vapor Density:1.2

Spec Gravity:0.99

pH:11

Evaporation Rate & Reference:0.3 (BUAC=1)

Solubility in Water:100

Appearance and Odor:C

LEAR BLUE LIQUID WITH SLIGHT AMMONIA ODOR.

===== **Stability and Reactivity Data**=====

Stability Indicator/Materials to Avoid:YES

===== **Disposal Considerations**=====

Waste Disposal Methods:DISPOSE ONLY IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.