

DEXTER ADHESIVES AND STRUCTURAL MATERIALS -- EA 9446 PART B -- 8040-01-175-9193
===== Product Identification =====

Product ID:EA 9446 PART B
MSDS Date:09/29/1989
FSC:8040
NIIN:01-175-9193
Kit Part:Y
MSDS Number: BJZZD
=== Responsible Party ===
Company Name:DEXTER ADHESIVES AND STRUCTURAL MATERIALS
Address:2850 WILLOW PASS ROAD
Box:312
City:PITTSBURG
State:CA
ZIP:94565
Country:US
Info Phone Num:41
5-687-4201
Emergency Phone Num:800-424-9300 (CHEMTREC)
Preparer's Name:SUZANNE FRANZ
CAGE:33564
=== Contractor Identification ===
Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address:2850 WILLOW PASS ROAD
Box:312
City:BAY POINT
State:CA
ZIP:94565-3299
Country:US
Phone:202-483-7616
CAGE:33564

===== Composition/Information on Ingredients =====

Ingred Name:ANILINE OLIGOMER

===== Hazards Identification =====

Routes of Entry: Inhal

ation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:MATERIAL IS TOXIC BY INGESTION.

Explanation of Carcinogenicity:N/K *BE BONDED. FAILURE TO OBSERVE

CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASES.

Effects of Overexposure:IRRITATION TO UPPER RESPIRATORY TRACT.

=====
===== First Aid Measures =====

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. WASH THOROUGHLY WITH SOAP AND WATER, RUBBING ALCOH

OL OR HAND CLEANER. DO

NOT USE SOLVENTS. IF INHALED, REMOVE TO FRESH AIR. IF INGESTED, SEEK MEDICAL A ID. REMOVE SOILED CLOTHING AND WASH BEFORE REUSE. IF IRRITATION PERSISTS, SEE PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:302F,150C

Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, WATER SPRAY, FOAM OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE LIBERATED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN AC CORDANCE WITH LABEL

INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG F) FOR 12 MONTHS.

Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Work Hygienic Practice

s:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

AVOID CONTACT WITH SKIN AND EYES. DO NOT HANDLE OR USE UNTIL THE MSDS HAS BEEN READ AND UNDERSTOOD.

===== Physical/Chemical Properties =====

Spec Gravity:0.97

Evaporation Rate & Reference:NIL

Solubility in Water:INSOLUBLE

Appearance and Odor:RED-BROWN LIQUID, CHARACTERISTIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRO

NG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:AVOID MIXING RESIN AND CURING AGENT IN BATCHES GREATER THAN 1 LB. DO NOT HEAT MIXED ADHESIVE UNLESS CURING SURFACES TO *

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (pr

vided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.