

SPARKLET DEVICES INC -- CARBON DIOXIDE -- 4220-00-372-0585

=====
Product Identification
=====

Product ID:CARBON DIOXIDE

MSDS Date:07/01/1989

FSC:4220

NIIN:00-372-0585

MSDS Number: BKBXG

=== Responsible Party ===

Company Name:SPARKLET DEVICES INC

Address:4400 GUSTINE AVE

City:ST LOUIS

State:MO

ZIP:63116-1712

Country:US

CAGE:87286

=== Contractor Identification ===

Company Name:JEFFERSON METALS STAMP
ING CO.

Address:4400 GUSTINE AVE

Box:City:ST LOUIS

State:MO

ZIP:53116-1712

Country:US

CAGE:0ZGE6

Company Name:SPARKLET DEVICES INC

Address:4400 GUSTINE AVE

Box:City:ST LOUIS

State:MO

ZIP:63116-1712

Country:US

Phone:314-353-0400

CAGE:87286

=====
Composition/Information on Ingredients
=====

Ingred Name:CARBON DIOXIDE

CAS:124-38-9

RTECS #:FF6400000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5000 PPM

ACGIH TLV:5000PPM/30000STEL;93

=====
Haza

rd Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SIMPLE ASPHYXIANT.HIGH CONCENTRATIONS OF CARBON DIOXIDE IN THE AMBIENT AIR CAN REDUCE THE OXYGEN CONTENT NECESSARY TO SUPPORT LIFE.IN THE SOLID PHASE(DRY ICE) CONTACT W/BODY TISSUE WILL PRODUCE COLD BURNS OR FROSTBITE W/IN SEVERAL SECONDS.

Explanation of Carcinogenicity:THIS MATERIAL IS NOT LISTED AS A

CARCINOGEN BY NTP, IARC, OSHA.

Effects of Overexposure:SHORTNESS OF BREATH,HEADACHE,DIZZINESS, WEAKNESS,DROWSINESS & RINGING IN EARS.DRY ICE IN CONTACT W/BODY TISSUE PRODUCES BURNING SENSATION;& FROSTBITE OCCURS W/IN SEVERAL SECONDS.

Medical Cond Aggravated by Exposure:CONDITIONS WHICH CAUSE BREATHING DIFFICULTY.

===== First Aid Measures =====

First Aid:DO NOT ATTEMPT TO REMOVE AN INDIVIDUAL FROM THE SCENE W/OUT UTILIZING PRO

PER RESCUE EQUIPMENT OR YOU MAY BECOME A CASUALTY.

MOVE VICTIM TO FRESH AIR WHILE KEEPING THEM WARM, DRY & QUIET. IF BREATHING HAS STOPPED PERFORM ARTIFICIAL RESPIRATION. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:MATERIAL IS AN EXTINGUISHING AGENT ITSELF.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:CONFINEMENT OF CARBON DIOXIDE IN VESSELS CONTAINERS OF IMP

ROPER DESIGN CAN RESULT IN EXPLOSION OR RUPTURE FROM OVER- PRESSURIZATION.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE THE AREA OF THE SPILL OR RELEASE, EMPLOY EMERGENCY FIRST AID PROCEDURES,PROVIDE PLENTY OF FRESH AIR.REMOV DRY ICE RESIDUAL & ALLOW TO SUBLIME IN A SECURED, WELL-VENTILATED AREA & CONTACT THE MANUFACTURER'S SAFETY DEPARTMENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== H

Handling and Storage =====

Handling and Storage Precautions:LIQUID & VAPOR STORAGE CONTAINERS ARE UNDER HIGH PRESSURE.DO NOT MIS-HANDLE OR ABUSE,CNTS.USE ONLY EQUIPMENT DESIGNED FOR CARBON DIOXIDE.

Other Precautions:AVOID DIRECT SKIN CONTACT WITH DRY ICE OR VENTING CARBON DIOXIDE LIQ OR VAPOR.USE PROTECTIVE EQUIP & CLOTHING AND GET PROPER TRAINING BEFORE HANDLING CARBON DIOXIDE IN CYLINDERS.

===== Exposure Controls/Personal Protection =====

R

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS- USE IN STRICT ACCORDANCE W/THE MANUFACTURER'S RECOMMENDATIONS.

Ventilation:FRESH AIR LOCAL EXHAUST/MECHANICAL

Protective Gloves:HEAVY TERRY-CLOTH TYPE

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment:SAFETY SHOES, HARD HATS & EAR PROTECTION SHOULD BE WORN WHEN WORKING W/PRESSURIZED CARBON DIOXIDE.

Work Hygienic Practices:PERSONS HANDLING CARBON DIOXIDE SHOULD BE FULLY TRAINED IN ADVANCE.

Supplemental Safety and Health

USE A PROPER PRESSURE REDUCING REGULATOR WHEN CONNECTING CYLINDER TO LOWER PRESSURE < 1500 PSIG. NEVER HEAT CYLINDER TO INCREASE DISCHARGE RATE. KEEP CYLINDERS UPRIGHT AND PROPERLY SECURED IN SECURED AREAS AWAY FROM HIGH TRAFFIC. HAVE ONLY QUALIFIED PERSONNEL REFILL CYLINDERS.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-109F,-79C

Vapor Pres:1 ATM

Vapor Density:1.5 AIR=1

Solubility in Water:90ML/100ML H2O

Appearance and Odor:IN SOLID TRANSLUCENT WHITE & ODORLESS.IN GAS & LIQ

COLORLESS & ODORLESS.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACTIVE ALKALI METALS(SUCH AS SODIUM, POTASSIUM, MAGNESIUM, ALUMINUM, TITANIUM, ZIRCONIUM), ORGANOMETALLICS, HYDRIDES.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:HEATING ABOVE 1700C CAUSES DECOMPOSITION O

F CARBON MONOXIDE & OXYGEN.

Conditions to Avoid Polymerization:IT CAUSES VIOLENT POLYMERIZATION OF
ACRYLALDEHYDE OR ETHLENEIMINE.

===== Disposal Considerations =====

Waste Disposal Methods:ALLOW CARBON DIOXIDE TO RELEASE, SUBLIME OR
DISSIPATE IN THE OPEN AIR.AVOID RELEASING IN COURTYARDS OR INDOORS
OR ANY AREAS WHERE HEAVY CARBON DIOXIDE VAPORS CAN ACCUMULATE.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.