

DOW CORNING CORP -- MOLYKOTE(R) 33 GREASE - MEDIUM -- 9150-00-584-4299

=====
Product Identification
=====

Product ID:MOLYKOTE(R) 33 GREASE - MEDIUM

MSDS Date:09/27/1985

FSC:9150

NIIN:00-584-4299

MSDS Number: BKCFL

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Nu

m:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country

:US
Phone:502-737-6757
CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:"NOT HAZARDOUS"
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT
TENDS TO REMOVE SKIN OILS AND MAY CAUSE SKIN IRRITATION. EXPOSURE
TO FUMES OR MI
STS MAY CAUSE MUCOUS MEMBRANE IRRITATION. EYES-MAY
CAUSE TEMPORARY DISCOMFORT.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:MILD IRRITATION OF SKIN AND MUCOUS MEMBRANE.

=====
First Aid Measures
=====

First Aid:SKIN-WIPE OFF EXCESS WITH SOAP AND WATER. EYE-FLUSH WITH
COPIOUS AMOUNTS OF WATER AND SEE A DOCTOR. INHALATION-REMOVE FROM
EXPOSURE TO FRE
SH AIR. INGESTION-ADMINISTER WATER AND SEEK MEDICAL
AID. DO NO T INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:>250F,121C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:CO

COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. RECOVER FREE
PRODUCT. ADD ABSORBENT MATERIAL SUCH AS CLAY TO SPILL AREA. SWEEP
OR SCRAPE UP.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. DO NOT STORE OR
MIX WITH OXIDIZING MATERIALS. AVOID EXCESS H

EAT OR FLAMES. HANDLE &

STORE USING METHODS USED FOR PETROLEUM PROD

Other Precautions:AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH
EYES AND INHALATION OF FUMES, VAPORS, OR MIST. DO NOT INGEST. WASH
THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED. RECOMMENDED IF FUMING OR
MISTING.

Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED TO CAPTURE HOT
FUMES. MECHANICAL (GENERAL) V

ENTILATION IS RECOMMENDED IF MISTIN

Protective Gloves:FOR PROLONGED OR REPEATED CONTACT.

Eye Protection:RECOMMENDED IF SPLASHING OR MISTING.

Other Protective Equipment:NORMALLT NOT REQUIRED.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR DRINKING. DO NOT
WEAR CONTAMINATED CLOTHING. REMOVE AND LAUNDRER BEFORE RE-USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres: