

TEMPIL BIG THREE INDUSTRIES, INC. -- TEMP-ALARM 44C -- 8010-01-124-9732

=====  
Product Identification  
=====

Product ID:TEMP-ALARM 44C

MSDS Date:07/19/1990

FSC:8010

NIIN:01-124-9732

MSDS Number: BKCYH

=== Responsible Party ===

Company Name:TEMPIL BIG THREE INDUSTRIES, INC.

Address:2901 HAMILTON BLVD.

City:SOUTH PLAINFIELD

State:NJ

ZIP:07080

Info Phone Num:(201) 757-8300

Emergency Phone Num:(201) 757

-8300

CAGE:FO789

=== Contractor Identification ===

Company Name:BIG THREE INDUSTRIES INC, TEMPIL DIV

Address:2901 HAMILTON BLVD

Box:City:SOUTH PLAINFIELD

State:NJ

ZIP:07080-2519

Country:US

Phone:908-757-8300

CAGE:82682

Company Name:TEMPIL BIG THREE INDUSTRIES, INC.

Address:2901 HAMILTON BLVD.

City:SOUTH PLAINFIELD

State:NJ

ZIP:07080

Phone:(201) 757-8300

CAGE:FO789

=====  
Composition/Information on Ingredients  
=====

Ingred Name:AMMONIUM DICHROMATE (BICHROMATE) (SARA III)

CAS:

7789-09-5

RTECS #:HX7650000

Fraction by Wt: 1-10%

OSHA PEL:0.1PPM CRO3;CEILING

ACGIH TLV:0.05 MG CR/M3

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 1-10%

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 75-85%

Other REC Limits:350 PPM (CL)

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EP

A Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)

CAS:123-91-1

RTECS #:JG8225000

Fraction by Wt: 1-5%

Other REC Limits:25 PPM

OSHA PEL:S, 100 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:VOL ORGANIC CMPD: 9.5 LBS/GAL

RTECS #:9999999VO

Ingred Name:NON-HAZARDOUS FOR INGREDIENTS

Fraction by Wt: 1-10%

=====  
===== Hazards Identification =====

Routes of Entry:

Inhalation: YES Skin: YES Ingestion: YES  
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO  
Health Hazards Acute and Chronic: SKIN: IRRITATION. INHALATION:  
IRRITATION OF NOSE, THROAT, NERVOUS SYSTEM DEPRESSION, HEADACHE,  
DROWSINESS, DIZZINESS, LOSS OF COORDINATION, & FATIGUE. INGESTION:  
IRRITATION & ASPIRATION HAZARD. EYE: PAIN & IRRITATION.  
Explanation of Carcinogenicity: NONE  
Effects of Overexposure: SKIN: IRRITATION. INHALATION: PERMANENT BRAIN &  
NERVOUS SYSTEM DAMAGE. EYE: PAIN & IRRITATION.

=====  
First Aid Measures  
=====

First Aid: EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN:  
WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION:  
ASPIRATION HAZARD. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION  
IN ALL CASES.

=====  
Fire Fighting Measures  
=====

Flash Point: NONE TO BOILING  
Extinguishing Media: DRY CHEMICAL, CO2, & FOAM.  
Fire Fighting Procedures: WEAR APPROPRIATE PROTECTIVE EQUIPMENT  
INCLUDING RESPIRATORY PROTECTION AS CONDITIONS WARRANT.  
Unusual Fire/Explosion Hazard: CONTAINER MAY EXPLODE IN HEAT OR FIRE.  
VAPORS ARE >AIR & MAY ACCUMULATE IN LOW AREAS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures: PICK UP IN ABSORBENT MATERIAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions: KEEP STORE CONTAINERS TIGHTLY CLOSED.  
STORE IN COOL, DRY AREA.  
USE IN WELL VENTILATED AREA. AVOID CONTACT  
W/EYES, SKIN, & CLOTHING.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection: NOT NECESSARY W/ADEQUATE VENTILATION.  
Ventilation: USE LOCAL EXHAUST. USE MECHANICAL VENTILATION IF LOCAL  
EXHAUST IS INADEQUATE.  
Protective Gloves: IMPERMEABLE  
Eye Protection: SPLASH GOGGLES  
Other Protective Equipment: AS REQUIRED  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

Boiling Pt: B.P. Text: 160-190F

Vapor Pres: 134

Vapor Density: 4.6

Spec Gravity: 1.3

Evaporation Rate & Reference: (N-BU AC = 1): 6

Solubility in Water: MODERATE

Appearance and Odor: YELLOW PAINT W/CHARACTERISTIC ODOR.

Percent Volatiles by Volume: 75-85%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS, OXIDIZING AGENTS, & REACTIVE METALS.

Stability Condition to Avoid: HEAT, FIRE, & HIGH PRESSURE IN ALUMINUM SYSTEMS.

Hazardous

Decomposition Products: CO, CO<sub>2</sub>, PHOSGENE, & HYDROGEN CHLORIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS CONCERNING HEALTH & ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.