View NSN Online: https://aerobasegroup.com/nsn/8030-00-262-9172

BAKER SEALANTS & COATINGS -- X532 WOOD FILLER -- 8010-00-262-9172

Product ID:X532 WOOD FILLER MSDS Date:01/01/1987 FSC:8010 NIIN:00-262-9172 MSDS Number: BKHKX === Responsible Party === **Company Name: BAKER SEALANTS & COATINGS** Address:234 SUYDAM AVE City: JERSEY CITY State:NJ ZIP:07304 Info Phone Num:(201) 333-6986 Emergency Phone Num: (201) 333-6986 CAGE:FO833 === Contractor Identification === Company Name: BAKER SEALANTS & COATINGS CO., INC. Address:234 SUYDAM AVENUE Box:B City: JERSEY CITY State:NJ ZIP:07304-3306 Phone: (201) 333-6986 CAGE:FO833 Company Name: BAKER SEALANTS AND COATINGS CO Address:234 SUYDAM AVE Box:City:JERSEY CITY State:NJ ZIP:07304-3306 Country:US Phone:201-333-6986 CAGE:34094

Ingred Name:WET NITROCELLULOSE, NITROCELLULOSE, NITRATE CELLULOSE CAS:9004-70-0 RTECS #:QW09 75200 Fraction by Wt: 9.3%

Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 7.4% Other REC Limits:400 PPM OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TEXTILE SPIRITS Fraction by Wt: 14.3%

Ingred Name:ACETONE (SARA III) CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 20.5% Other REC Limits:590 MG/CUM OSHA PEL:1000PPM ACGIH TLV:750PPM/1000STEL;9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANON E) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 29.5% Other REC Limits:590 MG/CUM OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:MAPLE FLOUR Fraction by Wt: 19%

Ingred Name:MODIFIERS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: HEADACH

E, NAUSEA, & LOSS OF CONSCIOUSNESS. SKIN: CHAPPING. EYE: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: HEADACHE, NAUSEA, & LOSS OF CONSCIOUSNESS. SKIN: CHAPPING. EYE: IRRITATION.
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN/EYES: FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Flash Point Method:TO C Flash Point:4F
Lower Limits:2.6%
Upper Limits:12.8% Extinguishing Media:ALCOHOL FOAM, CO2, & FOAM. Unusual Fire/Explosion Hazard:BURNS RAPIDLY W/INTENSE HEAT. FLAMMABLE LIQUID.
======================================
Spill Release Procedures:DIKE AREA. FLUSH W/WATER. SHOVEL INTO CONTAINERS.
======================================
Handling and Storage Precautions:STORE IN COOL AREA. GROUND ALL MIXING TANKS & DRUMS. DON'T AL LOW MATERIAL TO BECOME DRY.
======== Exposure Controls/Personal Protection ====================================
Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS. Ventilation:MECHANICAL; EXPLOSION PROOF MOTORS & SWITCHES. Protective Gloves:RUBBER Eye Protection:GOGGLES Other Protective Equipment:NORMAL CLOTHING
Supplemental Safety and Health
======================================
HCC:F3 Boiling Pt:B.P. Text:175F Spec Gravity:0.81

Evaporation Rate & amp; Reference: (BU

## AC =1): 7 Solubility in Water:SLIGHT Appearance and Odor: VISCOUS SOLUTION W/KEYTONIC ODOR.

Stability Indicator/Materials to Avoid:YES ALKALINE & STRONG ACIDS. Stability Condition to Avoid:HIGH HEAT Hazardous Decomposition Products:OXIDES OF NITROGEN.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. FLAMMABLE LIQUID. DOT UN1263.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their part

icular situation.