View NSN Online: https://aerobasegroup.kr/nsn/8030-00-778-4272

CROUSE-HINDS ECM DIV. COOPER INDUSTRIES -- CHICO A3 -- 8030-00-778-4272

Product ID:CHICO A3 MSDS Date:02/01/1989 FSC:8030 NIIN:00-778-4272 MSDS Number: BKHRK === Responsible Party === Company Name: CROUSE-HINDS ECM DIV. COOPER INDUSTRIES Address:WOLF & 7TH NORTH STREETS Box:4999 City:SYRACUSE State:NY ZIP:13221 Info Phone Num: (315) 477-7000 **Emergency Phone Num: (31** 5) 477-7000 CAGE:KO432 === Contractor Identification === Company Name: CROUSE-HINDS CO Address:WOLF AND 7TH N STS Box:4999 City:SYRACUSE State:NY ZIP:13221 Country:US Phone:315-477-7000 CAGE:15235 Company Name: CROUSE-HINDS ECM DIV., COOPER INDUSTRIES Address:WOLF & 7TH NORTH STREETS Box:4999 City:SYRACUSE State:NY ZIP:13221 Phone:315-447-7000 CAGE:KO432

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FOR

MS) (SARA III) CAS:1344-28-1 RTECS #:BD1200000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM OXIDE CAS:1305-78-8 RTECS #:EW3100000 OSHA PEL:5 MG/M3 ACGIH TLV:2 MG/M3; 9192

Ingred Name:IRON OXIDE CAS:1309-37-1 RTECS #:NO7400000 OSHA PEL:10 MG/M3 (FE) ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name: IRON OXIDE, FERROUS OXIDE CAS: 1345-25-1 OSHA PEL: 15 MG/CUM ACGIH TLV: 10 MG/CUM

Ingred Name:SILICA AMORPHOUS HYDRATED, SILICEOUS EARTH, FUMED SILICA, COLLOIDAL SILICON DI OXIDE, (SUSPECTED HUMAN CARCINOGEN) CAS:112945-52-5 RTECS #:VV7310000 Other REC Limits:20 MPPCF OSHA PEL:80 MG/CUM (%SIO2+2) ACGIH TLV:0.2 MG/CUM RESP/DUST

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:PORTLAND CEMENT CAS:65997-15-1 RTECS #:VV8770000 Other REC Limits:50 MPPCF (MSHA) OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Route

s of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: IRRITATION & BURNS. EYE: IRRITATION. INGESTION: OBSTRUCTION. Explanation of Carcinogenicity:NONE Effects of Overexposure:SKIN: IRRITATION & BURNS. EYE: IRRITATION. INGESTION: OBSTRUCTION.
======================================
First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/W ATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Flash Point:NON-COMBUSTIBLE
======================================
Spill Release Procedures: VACUUM WHERE POSSIBLE, OR SWEEP UP. MATERIAL WILL HARDEN IN PRESENCE OF WATER & MAY PLUG DRAINS. (HARDENING TIME IS 22-28 MINUTES). AVOID CREATING EXCESSIVE DUST.
======================================
Handl ing and Storage Precautions:STORE UNDER DRY CONDITIONS. DEW POINT CONDITIONS OR OTHER WET CONDITIONS DURING STORAGE WILL HARDEN SEALING COMPOUND. AVOID CREATING EXCESSIVE DUST.
======================================
Respiratory Protection:USE A NIOSH APPROVED NUISANCE DUST RESPIRATOR IF >TLV OR IN VERY DUSTY CONDITIONS. Ventilation:LOCAL EXHAUST: IF >TLV. OR OUTDOOR CONDITIONS. Protective Gloves:RECOMMENDED

Protective Gloves:RECOMMENDED

Eye Protection:DUST GOGGLES Other Protective E

quipment:AS REQUIRED Supplemental Safety and Health

HCC:B3 Melt/Freeze Pt:M.P/F.P Text:2372-2642F Spec Gravity:3 Solubility in Water:NEGLIGIBLE TO 0.2% Appearance and Odor:LIGHT GRAY, ODORLESS POWDER.

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:DEW, MOISTURE, & TEMPERATURES >2642F. Hazardous Decomposition Products:SULFUR DIOXIDE & CALCIUM OXIDE.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any

person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.