

CAAP CO., INC -- FLUOROELASTOMER RAIN, TYPES IV, 36270 -- 8013-01-127-1960

=====
Product Identification
=====

Product ID:FLUOROELASTOMER RAIN, TYPES IV, 36270

MSDS Date:03/16/1989

FSC:8013

NIIN:01-127-1960

MSDS Number: BKHXD

=== Responsible Party ===

Company Name:CAAP CO., INC

Address:152 PEPE'S FARM ROAD

City:MILFORD

State:CT

ZIP:06460

Info Phone Num:(203) 877-0375

Emergency Phone Num:(203) 877-

0375

Preparer's Name:RONALD D. ARENA

CAGE:MO997

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

Company Name:CAAP CO., INC

Address:152 PEPE'S FARM ROAD

City:MILFORD

State:CT

ZIP:06460

Phone:(203) 877-0375

CAGE:MO997

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Other

REC Limits:590 MG/CUM
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Other REC Limits:50 PPM
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:DIETHYLENE GLYCOL DIMETHYL ETHER
CAS:111-96-6
RTECS #:KN3339000
Other REC Limits:500 PPM

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Oth
er REC Limits:150 PPM
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Other REC Limits:3.5 MG/CUM (NIOSH)
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CHROMIUM (III) OXIDE (2:3)
CAS:1308-38-9
RTECS #:GB6475000
OSHA PEL:1 MG/CUM
ACGIH TLV:0.5 MG/CUM

Ingred Nam

e:CADMIUM SULFOSELENIDE
CAS:58339-34-7

Ingred Name:CADMIUM ZINC SULFIDE (YELLOW)
CAS:12442-27-2

Ingred Name:ALUMINUM CHROMIUM COBALT OXIDE
COBALT CHROMITE BLUE GREEN SPINEL
CAS:68187-11-1

Ingred Name:COBALT ALUMINATE BLUE
CAS:1345-16-0
OSHA PEL:0.1 MG/CUM
ACGIH TLV:0.1 MG/CUM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION TO NOSE,
THROAT/EYES, DIZZINESS, NAUSEA, NARCOSIS, HEADACHE, LOSS OF
APPETITE, REVERSIBLE TESTICULAR, SPERM DAMAGE, & TERATOGENICITY.
SKIN: IRRITATION, DERMATITIS, & BURNING. EYES: IRRITATION, &
BURNING. INGESTION: VOMITING.
Explanation of Carcinogenicity:CADMIUM & CADMIUM COMPOUNDS LISTED
SUSPECTED CARCINOGENS.
Effects of Overexposure:INHALATION: IRRITATION TO NOSE, THROAT/EYES,
DIZZINESS, HEADACHE, LOSS OF APPETITE, REVERSIBLE TESTICULAR,
SPERM
DAMAGE, NAUSEA, & TERATOGENICITY. SKIN: IRRITATION, DERMATITIS, &
BURNING. EYES: IRRITATION, & BURNING. INGESTION: VOMITING.
Medical Cond Aggravated by Exposure:ALLERGIES, ASTHMA, EYE/SKIN
DISORDERS

===== First Aid Measures =====

First Aid:EYES: FLUSH W/MUCH WATER. SKIN: WASH W/SOAP & WATER.
INHALATION: REMOVE TO FRESH AIR; GIVE ARTIFICIAL RESPIRATION.
INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL
CASES

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:35F

Lower Limits:1.4%

Upper Limits:10.0

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NOT MISCIBLE W/WATER, ALTHOUGH WATER MAY BE USED TO COOL FIRE EXPOSED CONTAINERS, FIRE FIGHTERS SHOULD WEAR FULL EMERGENCY EQUIPMENT INCLUDING SCBA.

Unusual Fire/Explosion Hazard:METHODS FOR FLAMMABLE LIQUIDS.

=====
===== Accidental Release Measures =====

===

Spill Release Procedures:KEEP IGNITION SOURCES AWAY. CONTAIN W/ABSORBENT MATERIAL. USE PROTECTIVE EQUIPMENT. CLEAN UP ABSORBANT & CONTAIN SECURELY. SWEEP & WET MOP W/SOAP & WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE