

NORTECH ADHESIVE CORP -- ADHESIVE MMM-A-130B -- 8040-00-779-9597

=====
Product Identification
=====

Product ID:ADHESIVE MMM-A-130B
MSDS Date:01/01/1991
FSC:8040
NIIN:00-779-9597
MSDS Number: BKJPL
=== Responsible Party ===
Company Name:NORTECH ADHESIVE CORP
Address:136 HALLADAY STREET
Box:5256
City:JERSEY CITY
State:NJ
ZIP:07305
Country:US
Info Phone Num:201-433-3766
Emergency Phone Num:201-433-3766
CAGE:0GD30
=== Contractor Identification ===
Company Name:NORTECH ADHESIVE CORP
Address:136 HALLADAY STREET
Box:5256
City:JERSEY CITY
State:NJ
ZIP:07305
Country:US
Phone:201-433-3766
CAGE:0GD30
Company Name:STEVEN INDUSTRIES
Address:39 AVENUE C
Box:8
City:BAYONNE
State:NJ
ZIP:07002-3417
Country:US
Phone:201-437-6501
CAGE:33150

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fra

ction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HEXANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
Fraction by Wt: 35%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:CAN CAUSE IRRITATION TO EYES, SKIN AND
RESPIRATORY TRACT.

===== First Aid Measures =====

F

irst Aid:SKIN CONTACT: WASH WITH WATER AND SOAP. EYE CONTACT: WASH WITH WATER AND CALL A PHYSICIAN. EXCESSIVE INHALATION: REMOVE TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:0F,-18C

Lower Limits:1.8

Upper Limits:1.5

Extinguishing Media:CO2.

Fire Fighting Procedures:IN CASE OF FIRE, USE FOG, FOAM, DRY CHEMICALS OR CO2.

Unusual Fire/Explosion Hazard:HANDLE AS VERY FLAMMABLE LIQ UID.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORBENT CLEANING SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT.

Other Precautions:NA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR APPROVED FOR ORGANIC SOLVENT.

Ventilation:USE LOCAL EXHAUST AS REQUIRED.

Protective Gloves:RUBBER & POLYETHYLENE

Eye Protection:GOGGLES TO PREVENT EYE CONTACT.

Other Protective Equipment:NA

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:132F,56C

Vapor Pres:186 MM HG

Vapor Density:NA

Spec Gravity:NA

Evaporation Rate & Reference:NA

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR LIQUID

Percent Volatiles by Volume:NA

===== Stability and Reac

tivity Data =====

Stability Indicator/Materials to Avoid: YES

NA

Stability Condition to Avoid: HEAT, SPARKS AND OPEN FLAMES.

Hazardous Decomposition Products: NA

===== Disposal Considerations =====

Waste Disposal Methods: FOLLOW FEDERAL AND LOCAL APPROVED ENVIRONMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.