

BAKER SEALANTS AND COATINGS CO, INC -- JOINT SEALING COMPOUND, X-555A & X-555B --  
8030-00-823-7972

===== Product Identification =====

Product ID:JOINT SEALING COMPOUND, X-555A & X-555B  
MSDS Date:12/18/1990  
FSC:8030  
NIIN:00-823-7972  
Kit Part:Y  
MSDS Number: BKJQB  
=== Responsible Party ===  
Company Name:BAKER SEALANTS AND COATINGS CO, INC  
Address:234 SUYDAM AVE  
Box:B  
City:JERSEY CITY  
State:NJ  
ZIP:073  
04  
Country:US  
Info Phone Num:201-333-6986  
Emergency Phone Num:201-333-6986  
Preparer's Name:CHARLES FRIEDMAN  
CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO  
Address:234 SUYDAM AVE  
Box:City:JERSEY CITY  
State:NJ  
ZIP:07304-3306  
Country:US  
Phone:201-333-6986  
CAGE:34094  
Company Name:STEVEN INDUSTRIES  
Address:39 AVENUE C  
Box:8  
City:BAYONNE  
State:NJ  
ZIP:07002-3417  
Country:US  
Phone:201-437-6501  
CAGE:33150

===== Composition/Information on Ingredients =====

=====

Ingred Name:COAL TAR PRODUCTS (PART A)  
CAS:65996-89-6  
RTECS #:GF8600100  
Fraction by Wt: 42%  
Other REC Limits:NONE SPECIFIED

Ingred Name:COAL TAR (PART B)  
CAS:65996-89-6  
RTECS #:GF8600100  
Fraction by Wt: 48%  
Other REC Limits:NONE SPECIFIED

Ingred Name:POLYOLS (PART B)  
Fraction by Wt: 50%  
Other REC Limits:NONE SPECIFIED

Ingred Name:PREPOLYMER (PART A)  
Fraction by Wt: 48%  
Other REC Limits:NONE SPECIFIED

Ingred Name:MISCELLANEOUS ADDITIVES  
Fraction by Wt: BALANCE  
Other REC Limits:NON  
E SPECIFIED

Ingred Name:VOC: 0  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:EYES: OVEREXPOSURE TO VAPORS CAN  
RESULT IN IRRITATION. EYE CONTACT W/PRODUCT WILL RESULT IN  
IRRITATION, WHICH CAN RESULT IN MINOR BURNS TO THE EYES. SKIN:  
CONTACT W/SKIN CAN RESULT IN IRRITATION WHICH CAN RESULT IN MINOR  
BURNS. INHALE: OVER  
EXPOSURE TO VAPOR MAY RESULT IN IRRITATION TO  
RESPIRATORY TRACT, ACUTE TOXIC \*  
Explanation of Carcinogenicity:COAL TAR: NTP CARCINOGENIC WITH POOR  
HYIGENE, INHALATION AND PROLONGED CONTACT OVER MANY YEARS.  
Effects of Overexposure:\*EFFECTS-RESPIRATORY DIFFICULTY, CONVULSION &  
CARDIOVASCULAR COLLAPSE. INGEST: IRRITATION OF THE GASTROINTESTINAL  
TRACT FOLLOWED BY NAUSEA AND VOMITING, ABDOMINAL DISCOMFORT, RAPID  
PULSE, ETC. CARDIOV ASCULAR COLLAPSE MAY OCCUR. FATAL DOSE IS ABOUT

0.1 G/KG OF BODY WEIGHT.  
Medical Cond Aggravated by Exposure:NONE

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER OR MINERAL OIL FOR AT LEAST 15 MIN. CALL DOCTOR. SKIN: REMOVE WITH WATERLESS HAND CLEANERS OR SOAP AND WATER. AVOID SOLVENTS. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. INGESTION: FIRST INDUCE VOMITING, THEN TAKE 2 TABLESPOONS OF ACTIVATED CHARCOAL-USP (DRUG GRADE) IN WATER. GET IMMEDIATE MEDICAL ASSISTANCE.

=====  
Fire Fighting Measures  
=====

Flash Point:>200F,>93C  
Extinguishing Media:EXTINGUISH WITH DRY CHEMICAL. WATER MAY CAUSE FROTHING.  
Fire Fighting Procedures:WHEN HEATED TO DECOMPOSITION EMIT LOW MOLECULAR WEIGHT COMPOUNDS.USE SELF-CONTAINED RESPIRATORY EQUIPMENT AND FULL PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:NOTIFY NATIONAL RESPONSE CENTER. DISPOSE OF BY MEANS OF BURIAL OR INCINERATION.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE BELOW 100F. USE GOOD HYGIENE AND HANDLE MATERIAL CAREFULLY.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR WITH SUITABLE ORGANIC VAPOR CARTRIDGE.  
Ventilation:REQUIRED, USE GOOD V

ENTILATION.

Protective Gloves:RUBBER GLOVES

Eye Protection:PROTECIVE GOGGLES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:160 TO 425F

Vapor Pres:0

Spec Gravity:1.12

pH:7-8

Viscosity:12000 KU

Solubility in Water:INSOLUBLE

Appearance and Odor:BLACK, COAL TAR ODOR

Percent Volatiles by Volume: