

=====
===== Product Identification =====

Product ID:FE-0004-B

MSDS Date:12/11/1988

FSC:8040

NIIN:00-998-3339

Kit Part:Y

MSDS Number: BKJTB

==== Responsible Party ===

Company Name:H.B. FULLER COMPANY

Address:1200 WOLTERS BLVD

City:VADNAIS HEIGHTS

State:MN

ZIP:55110

Country:US

Info Phone Num:612-481-3300

Emergency Phone Num:612-481-3300

CAGE:9R359

==== Contractor Identification ===

Company Name:H.B. FULLER COMPANY

Add

ress:3500 LEXINGTON AVENUE N.

Box:City:ST. PAUL

State:MN

ZIP:55126-8076

Country:US

Phone:612-236-5300/ -5309 FAX

CAGE:0DH19

Company Name:H.B. FULLER COMPANY-FOSTER PRODUCTS DIVISION

CAGE:9R359

=====
===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 1-10%

Other REC Limits:LEL: 2 %

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

Ingred Name:POLYAMIDE RESIN

Fraction by Wt: >10%

Other REC Limits:NONE SPECIFIED

==

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: STRONG IRRITANT. SKIN: SKIN
CONTACT WILL CAUSE SEVERE IRRITATION. STRONG DERMAL SENSITIZER.
INHALATION: INHALATION OF VAPORS MAY CAUSE RESPIRATORY IRRITATION.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH IMMEDIATELY WITH LARGE
AMOUNTS OF WATER FOR AT
LEAST 15 MINUTES. CALL A PHYSICIAN. SKIN: WASH AFFECTED AREA WITH
SOAP AND WATER. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.
INHALED: REMOVE FROM EXPOSURE. RESTORE BREATHING IF NECESSARY.
KEEP WARM & QUIET. CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:>200F,>93C
Extinguishing Media:USE WATER SPRAY, FOAM, DRY CHEMICAL OR CARBON
DIOXIDE.
Fire Fighting Procedures:PERSONS EXPO
SED TO PRODUCTS OF COMBUSTION
SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE
EQUIPMENT.

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR RUBBER GLOVES AND WIPE UP WITH ABSORBENT
MATERIAL. RESIDUE MAY BE REMOVED WITH A CHLORINATED SOLVENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL, DRY LOCATION.
Other Precautions:AVOID SKIN CONTACT WITH PR
ODUCT AT ALL TIMES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NORMALLY REQUIRED.
Ventilation:STANDARD INDUSTRIAL VENTILATION.
Protective Gloves:RUBBER GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:PREVENT CONTACT BY USING APPROPRIATE
PROTECTIVE CLOTHING.
Work Hygienic Practices:LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

==

Viscosity:75,000 CPS

Appearance and Odor:LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD LOW
MOLECULAR WEIGHT HYDROCARBONS, CARBON MONOXIDE, NITROGEN COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:THIS PRODUCT DOES NOT MEET THE DEFINITION OF
HAZARDOUS WASTE. INCINERATE OR DISPOSE OF IN AN APPROVED INDUSTRIAL
LANDFILL; CONSULT YOUR STATE OR LOCAL AUTHORITIES IN THE EVENT MORE
RESTRICTIVE REQUIREMENTS APPLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.