

MACKLANBURG-DUNCAN OF CALIFORNIA -- IRC R 35 WHITE RUBBER CEMENT PARTS A-B --  
8040-01-043-3196

===== Product Identification =====

Product ID:IRC R 35 WHITE RUBBER CEMENT PARTS A-B

MSDS Date:11/03/1986

FSC:8040

NIIN:01-043-3196

Kit Part:Y

MSDS Number: BKJTN

=== Responsible Party ===

Company Name:MACKLANBURG-DUNCAN OF CALIFORNIA

Address:15257 EAST PROCTOR AVENUE

City:CITY OF INDUSTRY

State:CA

ZIP:9

1745

Country:US

Info Phone Num:818-333-4578

Emergency Phone Num:818-333-4578

CAGE:MACKL

=== Contractor Identification ===

Company Name:MACKLANBURG-DUNCAN OF CALIFORNIA

Address:15257 EAST PROCTOR AVENUE

City:CITY OF INDUSTRY

State:CA

ZIP:91745

Country:US

Phone:818-333-4578

CAGE:MACKL

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN

Fraction by Wt: 66%

Other REC Limits:NONE SPECIFIED

Ingred Name:POLYMAMIDE RESIN (PART B)

Fraction by Wt: 100%

Other REC

Limits:NONE SPECIFIED

Ingred Name:EXPOXY PHENOL RESIN (PART A)

Fraction by Wt: 11%

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:A:LD50(DERMAL)>20M/KG(RAB) B:>8G/KG(RAB)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NOT KNOWN TO BE CARCINOGENIC.

Effects of Overexposure:SKIN: MAY IRRITATE SKIN.

=====  
First Aid Measures  
=====

First Aid:INHALATION:REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION. SKIN:WASH AFFECTED AREAS WITH PLENTY OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. DO NOT REUSE CLOTHING UNTIL THOROUGHLY CLEANED. INGESTION:DO NOT INDUCE VOMITING, CONTACT PHYSICIAN. EYES:IMMED FLUSH WITH PLENTY OF WATER FOR 15 MIN WHILE HOLDING EYELIDS OPEN. CALL PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC

Flash Point:430F,221C

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS IN POSITIVE PRESSURE MODE AND FULL PROTECTIVE GEAR SHOULD BE WORN.

Unusual Fire/Explosion Hazard:IRRITATING OR TOXIC GASES AND AEROSOLS MAY BE PRODUCED DURING BURNING.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SCRAPE INTO CONTAINERS AND DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE NEAR HEAT SOURCES, SPARKS, OR FLAME. STORE BETWEEN 40 AND 120 F. DO NOT FREEZE.

Other Precautions:DO NOT INGEST. KEEP AWAY FROM CHILDREN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NOT NECESSARY IN WELL VENTILATED AREA.

Ventilation:LOCAL EXHAUST: ADEQUATE TO KEEP BELOW TLV

Protective Gloves:NOT NECESSARY W/NORMAL PRECAUTIONS.

Eye Protection:RECOMMENDED

Work Hygienic Practices:WASH SKIN AND HANDS AFTER USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:> AIR

Spec Gravity:A:1.3 B:1.06

Evaporation Rate & Reference:> 1 (BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:YELLOWISH VISCOUS LIQUID

===== Stability and Reactivity Data =====

Stability Indi

cator/Materials to Avoid:YES

ACIDS, OXIDIZING AGENTS

Stability Condition to Avoid:OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS,  
MAY RELEASE HEAT UNDER THESE CONDITIONS.

Hazardous Decomposition Products:CARBON DIOXIDE, CO.

===== Disposal Considerations =====

Waste Disposal Methods:SANITARY LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The Unite

d States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.