

JET-LUBE INC. -- KOPR-KOTE (R) LEAD-FREE -- 8030-00-059-2761

=====  
Product Identification  
=====

Product ID:KOPR-KOTE (R) LEAD-FREE

MSDS Date:07/10/1991

FSC:8030

NIIN:00-059-2761

MSDS Number: BKMDH

=== Responsible Party ===

Company Name:JET-LUBE INC.

Address:4849 HOMESTEAD ROAD

Box:21258

City:HOUSTON

State:TX

ZIP:77226

Country:US

Info Phone Num:713-674-7617

Emergency Phone Num:713-674-7617

Prepare

r's Name:D A OLDIGES

CAGE:JO923

=== Contractor Identification ===

Company Name:JET-LUBE INC

Address:4849 HOMESTEAD RD

Box:21258

City:HOUSTON

State:TX

ZIP:77026

Country:US

CAGE:0A307

Company Name:JET-LUBE INC.

Address:4849 HOMESTEAD ROAD

Box:21258

City:HOUSTON

State:TX

ZIP:77226

Country:US

Phone:713-674-7617

CAGE:JO923

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM OIL

CAS:64741-96-4

RTECS #:PY8040000

Fraction by Wt: 70% MAX

Other REC Limits:NONE SPEC

IFIED  
OSHA PEL:5 MG/M3 (OIL MIST)

Ingred Name:COPPER POWDER (SARA III)  
CAS:7440-50-8  
RTECS #:GL5325000  
Fraction by Wt: 12% MAX  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:1 MG/M3  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:REPEATED SKIN CONTACT FOR PERSONS  
HYPERSENSITIVE TO PETROLEUM PRODUCTS CAN CAUSE REDNESS AND  
IRRITATION OF SKIN.  
Ef  
fects of Overexposure:REDNESS AND IRRITATION OF SKIN.

===== First Aid Measures =====

First Aid:INHALATION: CLEAR AIR PASSAGES, CALL PHYSICIAN. INGESTION: IF  
INGESTED, CALL PHYSICIAN. EYES: WASH WITH COPIOUS QUANTITIES OF  
WATER. SKIN: REMOVE BY WIPING, OR WATERLESS HAND CLEANER, FOLLOWED  
BY WASH ING.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:465F,241C  
Autoignition Temp:Autoignition  
Temp Text:500F  
Extinguishing Media:USE FOAM, DRY CHEMICAL, WATER SPRAY (FOG), CARBON  
DIOXIDE OR VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.  
Fire Fighting Procedures:USE SUPPLIED-AIR BREATHING EQUIPMENT FOR  
ENCLOSED OR CONFINED SPACES.  
Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS, WIPE UP WITH RAGS, PICK-UP  
RESIDUE WITH DIATOMACEOUS EARTH TO AVOID WALKING HAZARD.

=====

=== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS AS WITH ANY  
PETROLEUM PRODUCT.

===== Exposure Controls/Personal Protection =====

Other Protective Equipment:PERSONS WITH HYPERSENSITIVE SKIN SHOULD USE  
GLOVES.

Work Hygienic Practices:WASH HANDS BEFORE EATING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:624F,329C

Vapor Pres:5

Spec Gr

avity:1.14 (WATER=1)

Evaporation Rate & Reference: