

COLUMBIA CHASE CORP. HUMISEAL DIV. -- 2A64 HUMISEAL PART A -- 5970-01-013-8611

=====
Product Identification
=====

Product ID:2A64 HUMISEAL PART A

MSDS Date:09/29/1989

FSC:5970

NIIN:01-013-8611

MSDS Number: BKQWN

=== Responsible Party ===

Company Name:COLUMBIA CHASE CORP. HUMISEAL DIV.

Address:26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:445

City:WOODSIDE

State:NY

ZIP:11377-0445

Country:US

Info Phone

Num:718-932-0800

Emergency Phone Num:718-932-0800

CAGE:EO647

=== Contractor Identification ===

Company Name:COLUMBIA CHASE CORPORATION

Box:445

CAGE:EO647

Company Name:HUMISEAL DIVISION/CHASE CORPORATION

Address:26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:City:WOODSIDE

State:NY

ZIP:11377

Country:US

Phone:718-932-0800

CAGE:99109

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

=====
Compos

ition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 14 - 21%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE
CAS:108-65-6
RTECS #:AI8295000
Fraction by Wt: 26 -30%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPN

Ingred Name:ETHYL ACETATE (SARA III)
CAS:141-78-6
RTECS #:AH5
425000
Fraction by Wt: 1 - 2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POLYESTERS, PROPRIETARY
RTECS #:9999999ZZ
Fraction by Wt: 42 - 50%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:IRRITATION IF THE NOSE, THROA

T, EYES,
LUNGS AND SKIN. UNUSUAL OR LABORED OR ASTHMA-LIKE BREATHING,
CARDIAC ABNORMALITY.

Effects of Overexposure:SEE HEALTH HAZARDS

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:REMOVE SATURATED CLOTHING, WASH SKIN WITH GREEN TINCTURE OF
SOAP, FLUSH EYES 15 MINUTES WITH CLEAR WATER, REMOVE PATIENT TO
FRESH AIR. CALL A PHYSICIAN.

===== Fire Fighting Measures

=====

Flash Point Method:TCC

Flash Point:27.0F,-2.8C

Lower Limits:1.4

Upper Limits:6.7

Extinguishing Media:DRY CHEMICAL, FOAM, CARBON DIOXIDE. WATER MAY BE
INEFFECTIVE.

Fire Fighting Procedures:FIGHT AS FLAMMABLE LIQUID.

Unusual Fire/Explosion Hazard:VAPOR IS FLAMMABLE AND HEAVIER THAN AIR
AND MAY TRAVEL TO SOURCE OF IGNITION AND FLASHBACK. USE WATER TO
KEEP FIRE EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.

===== Accidental Release Measures =====

=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. PROVIDE
VENTILATION AND/OR RESPIRATORY PROTECTION. ABSORB SMALL SPILLS WITH
AN INERT MATERIAL OR PICK UP LARGE SPILLS WITH NON SPARKING TOOLS.
RESIDUES MAY BE CLEANED UP WITH ALCOHOL/WATER OR AMMONIA
SOLUTIONS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT, SPARKS AND OPEN
FLAME. AVOI

D PROLONGED SKIN CONTACT. DON'T BREATH SPRAY MISTS.

GROUND CONTAINERS WHILE POURING.

Other Precautions:EMPTIED CONTAINERS MAY RETAIN HAZARDOUS PROPERTIES.
DO NOT CUT, PUNCTURE OR WELD ON OR NEAR THE CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MASK OR RESPIRATORS FOR ORGANIC VAPOR
AND PARTICULATE.

Ventilation:LOCAL EXHAUST. EXPLOSION PROOF MECHANICAL VENTILATION.

Protective Gloves:SOLVENT RESISTANT

Eye Protection:CHE

MICAL GOGGLES

Other Protective Equipment:EYE WASH AND SAFETY SHOWER

Work Hygienic Practices:WASH HANDS AFTER USING THIS PRODUCT.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt.=141.1C, 286.F

Vapor Pres:14

Vapor Density:4.6

Spec Gravity:1.03

Evaporation Rate & Reference:1.78 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LOW VISCOSITY, STRAW COLORED LIQUID WITH AROMATIC
ODOR.

Percent Vola

tiles by Volume:40-50

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE AND
POSSIBLY OXIDES OF NITROGEN AND ACROLEIN.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF HUMISEAL PRODUCTS REQUIRES STRICT
COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS PERTAINING TO
DISPOSIN

G HAZARDOUS WASTE MATERIALS. CONTACT THE APPROPRIATE ENVIRONMENTAL AGENCIES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume r

esponsibility for the suitability of this information to their particular situation.