

TEXWIPE CO -- ALCOPAD, PRODUCT NUMBER TX806 -- 7035-01-321-7456

=====  
Product Identification  
=====

Product ID:ALCOPAD, PRODUCT NUMBER TX806

MSDS Date:01/01/1991

FSC:7035

NIIN:01-321-7456

MSDS Number: BKQYC

=== Responsible Party ===

Company Name:TEXWIPE CO

Address:650 E CRESENT AVE

Box:575

City:UPPER SADDLE RIVER

State:NJ

ZIP:07458-1827

Country:US

Info Phone Num:201-327-9100

Emergency Phone Num:80

0-284-5577; 800-424-9300 CHEMTREC

Preparer's Name:SCOTT FAHY

CAGE:21994

=== Contractor Identification ===

Company Name:TELEPRINTER CORP OF AMERICA

Address:550 SPRINGFIELD AVE

Box:City:BERKLEY HEIGHTS

State:NJ

ZIP:07922-1016

Country:US

Phone:201-464-5310

CAGE:60037

Company Name:TEXWIPE CO

Address:650 E CRESENT AVE

Box:308

City:UPPER SADDLE RIVER

State:NJ

ZIP:07458-1827

Country:US

Phone:201-327-5577

CAGE:21994

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPR

OPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 91%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:MILD IRRITATION TO THE NOSE AND  
THROAT. PROLONGED EXPOSURES ABOVE THE TLV MAY CAUSE NARCOSIS,  
NAUSEA AND HEADACHE.  
EYE CONTACT WILL CAUSE LOCAL IRRITATION AND  
BURNING SENSATIONS, WITH POSSIBLE DAMAGE. SKIN CONTACT WILL CAUSE  
A STINGING ANDBURNING SENSATION WITH DEFATTING AND POSSIBLE  
IRRITATION FROM PORLONGED CONTACT.  
Effects of Overexposure:SEE SIGNS AND SYMPTOMS.  
Medical Cond Aggravated by Exposure:NONE LISTED

=====  
===== First Aid Measures =====  
=====

First Aid:EYES: IRRIGATE WITH WATER FOR 15 MINUTES, INCLUDING UNDER  
EYELIDS. GET MEDICAL HELP. SKIN: FLUSH WIT  
H WATER. INHALATION:  
REMOVE TO FRESH AIR. RESTORE AND/OR SUPPORT BREATHING AS NEEDED.  
GIVE OXYGEN IF BREATHING IS DIFFICULT. INGESTION: GET PROMPT  
MEDICAL HELP. GIVE WATER TO DRINK TO DILUTE. IF MEDICAL HELP IS NOT  
READILY AVAILABLE, INDUCE VOMITING IF PATIENT IS ALERT.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:TCC  
Flash Point:60.0F,15.6C  
Lower Limits:2  
Upper Limits:12  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR ALCOHOL F  
OAM. WATER  
MAY BE USED TO COOL FIRE EXPOSED CONTAINERS.  
Fire Fighting Procedures:FINE WATER MIST MAY BE USED TO SMOTHER FIRE OR  
DISPERSE VAPORS.  
Unusual Fire/Explosion Hazard:LIQUID MAY RELEASE FLAMMABLE VAPORS WHICH  
CAN IGNITE AT OR ABOVE FLASH POINT.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:CLEAN-UP PERSONNEL NEED PROTECTION AGAINST  
LIQUID CONTACT AND VAPOR INHALATION. ABSORB SMALL SPILLS WITH PAPER  
TOWELS, EVAPORATE FLA

FLAMMABLE ALCOHOL IN EXHAUST HOOD AND BURN DRY  
PAPER. CONTAIN LARGE SPI LLS AND ABSORB WITH AN INERT MATERIAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN, COOL, VENTILATED  
AREA AWAY FROM SOURCES OF IGNITION AND OXIDIZING AGENTS. STORE  
ACCORDING TO AN OSHA CLASS 1B FLAMMABLE LIQUID.  
Other Precautions:DO NOT SMOKE OR EAT IN AREAS OF STORAGE OR USE.

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED UNDER NORMAL USE.  
Ventilation:PROVIDE GENERAL VENTILATION (EXPLOSION-PROOF) TO MEET TLV  
REQUIREMENTS.  
Protective Gloves:NOT NEEDED UNDER NORMAL CONDITIONS.  
Eye Protection:NOT NEEDED UNDER NORMAL CONDITIONS.  
Other Protective Equipment:WHEN CONTACTING LARGE VOLUMES, WEAR LONG  
SLEEVES, CHEMICAL GLOVES, CHEMICAL GOGGLES AND LONG SLEEVES.  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.  
Supplement  
al Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:F2  
Boiling Pt:=27.5C, 81.5F  
Vapor Pres:43  
Vapor Density:>1  
Spec Gravity:0.818  
Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)  
Solubility in Water:COMPLETE  
Appearance and Odor:PRESATURATED PAD. CLEAR LIQUID WITH ALCOHOL ODOR.  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
CAUSTICS, AMINES, ALK

ANOLAMINES, ALDEHYDES, AMMONIA, STRONG OXIDIZING  
AGENTS AND CHLORINATED COMPOUNDS.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS AND FLAMES.

Hazardous Decomposition Products:CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:BURN WASTE LIQUID IN AN APPROVED INCINERATOR OR  
DISPOSE OF VIA LICENSED WASTE DISPOSAL COMPANY. ABSORBED LIQUID  
CAN BE LANDFILLED. FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (prov

ided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.