View NSN Online: https://aerobasegroup.kr/nsn/3439-00-452-0374

Product ID:SOLDER ALLOY OF TIN MSDS Date:03/13/1990 FSC:3439 NIIN:00-452-0374 MSDS Number: BKSRL === Responsible Party === Company Name: ALPHA METALS Address:600 ROUTE 440 City: JERSEY CITY State:NJ ZIP:07304 Country:US Info Phone Num:201-434-6778 Emergency Phone Num:201-434-6778, CHEMTREC 800-424-9300 CAGE:96 613 === Contractor Identification === **Company Name: DEANCO INC** Address:7933 QUEENAIR DR Box:City:GAITHERSBURG State:MD ZIP:20879-4137 Country:US Phone:301-948-5444 CAGE:9K946 Company Name: FRYS METALS INC (FORMER ALPHA METALS) Address:600 ROUTE 440 Box:City:JERSEY CITY State:NJ ZIP:07304 Country:US Phone:201-434-6778 CAGE:96613

Ingred Name:TIN CAS:7440-31-5 RTECS #:XP7320000 Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/M3 ACGI H TLV:2 MG/M3; 9192

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:SILVER (SARA III) CAS:7440-22-4 RTECS #:VW3500000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH CAS:7440-69-9 RTECS #:EB2600000 Other REC Limits:NONE SPECIFIED

Ingred Name:INDIUM CAS:7440-7 4-6 RTECS #:NL1050000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3; 9192

Ingred Name:ANTIMONY (SARA III) CAS:7440-36-0 RTECS #:CC4025000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG SB/M3; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic

 :ACUTE-INHALATION OF FUMES(DURING SOLDERING):IRRITATION OF EYES AND RESPIRATORY TRACT SYSTEM. CHRONIC:LONG AND REPEATED EXPOSURE TO METAL FUMES MAY CAUSE HEADACHE, NAUSEA/VOMITING, ACHING BONES, FATIGU E, DECREASED APPETITE, ABDOMINAL CRAMPING, ANEMIA, BRAIN, HEART, LUNG, LIVER AND KIDNEY DEGENERATIVE CHANGES. Effects of Overexposure:EXPOSURE TO FUMES MAY RESULT IN IRRITATION OF NOSE, THROAT, EYES AND SKIN. BURNS FROM SKIN CONTACT OF MOLTEN SOLDER. WATERY EYES, HEADAC HE, BREATHING DIFFICULTY, FREQUENT COUGHING. Medical Cond Aggravated by Exposure:SOME WORKERS WITH PRE-EXISTING
CONDITIONS OF LUNGS, EYES, SKIN, AND THOSE PREVIOUSLY EXPOSED TO LEAD & ANTMONY MAY BE AT INCREASED RISK.
======================================
First Aid:SKIN BURNS:FLUSH WITH COLD WATER OR APPLY ICE. IN CASE OF SEVERE BURNS GET MEDICAL HELP. EYE IRRITATION:FLUSH WITH WATER FOR 15 MINUTES. INHALATION:REMOVE TO FRESH AIR. ADMINISTER O XYGEN IF
BREATHING IS DIFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. GET MEDICAL HELP. INGESTION:GET MEDICAL HELP.
======================================
Extinguishing Media:USE DRY CHEMICAL. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUC F
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.
======================================
Spill Release Procedures: CLEAN UP ANY DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSURE. Neutralizing Agent: NONE
======================================

Handling and Storage Precautions:NO SPECIAL REQUIREME

NTS FOR STORAGE. WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN SOLDERING. Other Precautions:DO NOT INHALE FUMES.

Respiratory Protection: USE FUME/ORGANIC VAPOR RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN SOLDERING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS. Ventilation: USE ENOUGH VENTILATION WHEN SOLDERING TO KEEP THE DUST, FUMES & GASES BELOW TLV. Protective Gloves:LEATHER GLOVES Eve Protection: OSHA APPROVED GOGGLES/FACE SHIELD Other Protective Equipment: FLAME RETARDANT CLOTHING AND LEATHER GLOVES WHEN SOLDERING. Work Hygienic Practices: WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDER CONTAMINATIED CLOTHING BEFORE REUSE. Supplemental Safety and Health HCC:N1 Solubility in Water: INSOLUBLE Appearance and Odor:SILVE R GREY WIRE, ODORLESS. VARIOUS SHAPES AND SIZES. Stability Indicator/Materials to Avoid:YES STRONG ACIDS AND BASES Stability Condition to Avoid:NONE

Hazardous Decomposition Products: TOXIC METAL FUMES ABOVE 886C(1627F).

Waste Disposal Methods:DISPOSE OF ACCORDING TO FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by th

e compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.