

CIBA-GEIGY CORP REN PLASTICS DIV -- EPOCAST 31A A, PRODUCT CODE FPC2055 --
9330-00-738-2626

=====
===== Product Identification =====

Product ID:EPOCAST 31A A, PRODUCT CODE FPC2055

MSDS Date:02/08/1990

FSC:9330

NIIN:00-738-2626

Kit Part:Y

MSDS Number: BKSSW

=== Responsible Party ===

Company Name:CIBA-GEIGY CORP REN PLASTICS DIV

Address:4917 DAWN AVE

City:EAST LANSING

State:MI

ZIP:48823-5605

Country:US

|

Info Phone Num:914-478-3131

Emergency Phone Num:914-479-5000

Preparer's Name:RAJESH S. PATEL

CAGE:0267X

=== Contractor Identification ===

Company Name:CIBA-GEIGY CORP

Address:4917 DAWN AVE

Box:18300

City:EAST LANSING

State:MI

ZIP:48823-5605

Country:US

Phone:517-351-5900

CAGE:0267X

Company Name:MCGEAN-ROHCO INC

Address:5621 COMMONWEALTH

City:DETROIT

State:MI

ZIP:48208-1742

Country:US

CAGE:02984

=====
===== Composition/Information on Ingredients =====

Ingred Name:VINYL CYCLOHEXENE DIO

XIDE
CAS:106-87-6
RTECS #:RN8640000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 10 PPM
ACGIH TLV:S, 10 PPM ;A2; 9192

Ingred Name:PHENOL-FORMALDEHYDE POLYMER, GLYCIDYL ETHER
CAS:28064-14-4
Fraction by Wt: 75%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS UNKNOWN.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards

Acute and Chronic:MAY CAUSE SEVERE EYE IRRITATION ON
DIRECT CONTACT. VAPORS FROM HEAT CURE AND DUST FROM GRINDING,
SANDING, ETC. MAY CAUSE EYE AND RESPIRATORY SYSTEM IRRITATION.
PROLONGED OR REPEATED SKIN CONTACT MAY PRODUCE SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION. INGESTION MAY CAUSE DIGESTIVE
SYSTEM IRRITATION.

Effects of Overexposure:MAY CAUSE EYE, SKIN & RESPIRATORY TRACT
IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION IN CERTAIN
SUSCEPTIBLE INDIVIDU

ALS. INGESTION MAY CAUSE NAUSEA, VOMITING, AND
DIARRHEA.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING SKIN
DISORDERS ARE AT A GREATER THAN NORMAL RISK WHEN EXPOSED TO THIS
MATERIAL.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE PERSON TO FRESH AIR. CALL A PHYSICIAN.
EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.
GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH
WIT

H SOAP AND WATER PROMPTLY. INGESTION: DO NOT INDUCE VOMITING.
GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>225F,>107C

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER SPRAY.

Fire Fighting Procedures:WEAR BREATHING APPARATUS AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:DECOMPOSITION OR COMBUSTION MAY PRODUCE TOXIC PRODUCTS. HEAT CAN CAUSE POLYMERIZATION. HEATED SEAL

ED

CONTAINERS CAN EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. COLLECT SPILLED MATERIALS.

PLACE IN A US DOT APPROVED METAL CONTAINER AND SEAL.

Neutralizing Agent:MIX PART A WITH PART B.

===== Handling and Storage =====

Handling and Storage Precautions:PREVENT CONTACT WITH EYES AND SKIN.

KEEP CONTAINER CLOSED WHEN NOT IN USE. FOR INDUSTRIAL OR PROFESSIONAL USE ONLY. FOR

IMMEDIATE USE WHEN MIXED.

Other Precautions:THIS PRODUCT CONSISTS OF TWO COMPONENTS. THE

PRECAUTIONS FOR EACH COMPONENT SHOULD BE OBSERVED WHEN SEPARATE OR MIXED. KEEP OUT OF THE REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED DUST RESPIRATOR WHEN GRINDING OR SANDING CURED MATERIAL.

Ventilation:PROVIDE SUFFICIENT LOCAL & MECHANICAL(GENERAL) VENTILATION IN PATTERN/VOLUME

TO CONTROL INHALATION EXPOSURES.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:CHEMICAL SAFETY GOGGLES

Other Protective Equipment:WEAR INDUSTRIAL-TYPE WORK CLOTHING.

Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

THIS IS A TWO PART PRODUCT. EMPTY CONTAINERS MAY RETAIN PRODUCT RESIDUE OR VAPORS. AIRBORNE PARTICULATE MAY BE GENERATED DURING REMOVAL OPERATIONS INCLUDING ABRA

SIVE BLASTING, SANDING OR GRINDING.

===== Physical/Chemical Properties =====

HCC:T4

Vapor Pres: