

D-A LUBRICANT CO INC SUB OF PREMIER INDUSTRIAL -- HYDRATRANS 135 -- 9150-01-177-9438  
===== Product Identification =====

Product ID:HYDRATRANS 135

MSDS Date:03/30/1990

FSC:9150

NIIN:01-177-9438

MSDS Number: BKTCB

=== Responsible Party ===

Company Name:D-A LUBRICANT CO INC SUB OF PREMIER INDUSTRIAL

Address:1340 W 29TH ST

City:INDIANAPOLIS

State:IN

ZIP:46208-4943

Country:US

Emergency Phone Num:317-9

23-5321/216-391-8300 OTHER HRS

CAGE:30719

=== Contractor Identification ===

Company Name:D-A LUBRICANT CO INC SUB OF PREMIER INDUSTRIAL

Address:1340 W 29TH ST

Box:City:INDIANAPOLIS

State:IN

ZIP:46208-4943

Country:US

Phone:317-923-5321/216-391-8300 OTHER HRS

CAGE:30719

===== Composition/Information on Ingredients =====

Ingred Name:SOL.REF.HYDROTREATED HEAVY PARAFFINIC DIST./PETROLEUM OILS  
(INGREDIENTS 1 & 2 TOTAL 60-99%).

CAS:64742-54-7

Other REC Limits:NONE SPECIFIED

OSHA

PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:REFINED HEAVY PARAFFINIC DISTILLATES/PETROLEUM OILS  
(INGREDIENTS 1 & 2 TOTAL 60-99%).

CAS:64741-88-4

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:BUTYL BENZYL PHTHALATE (SARA III)

CAS:85-68-7

RTECS #:TH9990000

Fraction by Wt: 0.1 - 1%

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ZINC DIALKYL DITHIOPHOSPHATE

CAS:68457-79-4

Fracti

on by Wt: 0.5-1.5%

Other REC Limits:NONE SPECIFIED

Ingred Name:ACRYLIC COPOLYMER (OSHA NONHAZARDOUS)

Fraction by Wt: > 1%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 12000 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-MAY CAUSE RESPIRATORY SYSTEM,SKIN AND/OR EYE IRRITATION.INGESTION MAY CAU

SE

NAUSEA,CRAMPS,DIARRHEA,AND OTHER GASTROINTESTINAL

DISORDERS.CHRONIC-EXCESS MIST MAY CAUSE RESPIRATORY PROBLEMS.EXCESS

SKIN CONTACT MAY CAUSE DRYNESS.

Effects of Overexposure:SEE HEALTH HAZARDS SECTION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:CONSULT A PHYSICIAN.INHALATION:REMOVE TO FRESH AIR.GIVE

OXYGEN IF NECESSARY.EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 1

5 MINUTES HOLDING EYELIDS OPEN.SKIN:REMOVE CONTAMINATED

CLOTHING.WASH SKIN WITH SOAP AND WATER.INGESTION:DO NOT INDUCE VOMITING.GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:>370F,>188C

Autoignition Temp:Autoignition Temp Text:>500F

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL, SAND OR EARTH. TREAT AS A CLASS B FIRE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A

FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCE IF SAFE TO DO SO.PREVENT FROM

ENTERING WATERWAYS & DRAINS.WEAR SUITABLE PERSONAL PROTECTIVE

EQUIPMENT.DIKE AND ABSORB WITH INERT MATERIAL AND TRANSFER TO A

SEALED APPROVED CONTAINER FOR DISPOSAL. REPORT ANY SPILL IF ENTER WATER(NRC).

=====

Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN A COOL & VENTILATED AREA AWAY FROM HEAT,FLAMES & STRONG OXIDANTS.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. FOLLOW DIRECTIONS ON PRODUCT LABEL. EMPTY CONTAINERS RETAIN RESIDUE WHICH CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL/EXPOSE TO HEAT, FLAME .. THEY MAY EXPLODE AND CAUSE INJURY/DEATH.

===== Exposure Controls/Personal Protection ===

=====

Respiratory Protection:USE ONLY IN WELL VENTILATED AREAS. IF VENTILATION IS INADEQUATE, WEAR OSHA APPROVED RESPIRATORY EQUIPMENT.

Ventilation:LOCAL/MECHANICAL

Protective Gloves:OIL/SOLVENT RESISTANT

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:EYE WASH FOUNTAIN AND SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER USING. AVOID PROLONGED/REPEATED BREATHING OF FUMES,VAPORS/MIST.AVOID CONTACT WITH EYES AND SKIN.

Supplemental  
Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C

Vapor Pres:NIL

Spec Gravity:0.86 TO 0.90

Evaporation Rate & Reference:< 0.1 (WATER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT BROWN FLUID WITH MILD PETROLEUM ODOR

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condi

on to Avoid:HIGH HEAT, OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE AND SOX

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. THE PHONE NUMBER FOR NATIONAL RESPONSE CENTER (NRC) IS 800-424-8802.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the D

epartment

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.