

FLAMEMASTER CORP -- CS 3300 (PART B) -- 8030-00-616-9191

=====
Product Identification
=====

Product ID:CS 3300 (PART B)

MSDS Date:03/16/1990

FSC:8030

NIIN:00-616-9191

MSDS Number: BKYMC

=== Responsible Party ===

Company Name:FLAMEMASTER CORP

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Info Phone Num:(818) 982-1650

Emergency Phone Num:(818) 982-1650

CAGE:14439

=== Contractor Ident

ification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD PEROXIDE, LEAD DIOXIDE

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 64%

OSHA PEL:50 UG/CUM

ACGIH TLV:0.15 MG/CUM

Ingred Name:LEAD OXIDE YELLOW, LEAD OXIDE

CAS:1317-36-8

RTECS #:OG1750000

Fraction by Wt: 6%

OSHA PEL:0.05 MG/CUM

ACGIH TL

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. INGESTION: WEAKNESS,
STUPOR, KIDNEY DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS, HEADACHE,
MUSCLE & JOINT PAIN & NEUROMUSCULAR DYSFUNCTION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES: IRRITATION. INGESTION: WEAKNESS, STUPOR,
KIDNE
Y DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS, HEADACHE, MUSCLE &
JOINT PAIN & NEUROMUSCULAR DYSFUNCTION.
Medical Cond Aggravated by Exposure:ANEMIA, KIDNEY DISEASE & PREGNANCY

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/PLENTY OF WATER. INGESTION: INDUCE VOMITING.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>200F
Extinguishing Media:DRY CHEMICAL, FOAM, CO2 OR WATER
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS W/FULL
FACEPIECE, IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT
W/OXIDIZABLE MATERIALS AT HIGH TEMPERATURES

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP & TRANSFER TO SAFETY CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY AREA. KEEP
CONTAINERS CLOSED WHEN NOT USING. TRAIN EMPLOYEES IN THE SAFE
HANDLING OF THIS PRODUCT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF SUSTAINED USE NIOSH APPROVED RESPIRATOR
Ventilation:PROVIDE LOCAL AIR HOOD OR MECHANICAL FAN EXHAUST
VENTILATION
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR DRINKING
AFTER HANDLING
Supplemental Safety and Health
EXPOSURE

LIMITS ARE BASED ON DUST PARTICLES. THE LEAD DIOXIDE/OXIDE PARTICLES ARE WETTED OUT, THEREFORE AIRBORNE PARTICLES WILL NOT RESULT FROM NORMAL USE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:644F
Melt/Freeze Pt:M.P/F.P Text:ROOM TEMP.
Vapor Pres:NIL
Spec Gravity:3
Evaporation Rate & Reference:NIL
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BROWN PASTE W/OILY ODOR

===== Stability and Reactivity Data =====

==

Stability Indicator/Materials to Avoid:YES
OXIDIZABLE MATERIALS
Stability Condition to Avoid:HIGH TEMPERATURES & HEAT
Hazardous Decomposition Products:LEAD OXIDE DUST & ORGANICS

===== Disposal Considerations =====

Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT W/BASE. DISPOSE OF ACCORDING TO FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated
for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.