

GLYPTAL INC -- GLYPTAL -- 5970-00-900-9372

===== Product Identification =====

Product ID:GLYPTAL  
MSDS Date:07/14/1994  
FSC:5970  
NIIN:00-900-9372  
MSDS Number: BKYNX  
=== Responsible Party ===  
Company Name:GLYPTAL INC  
Address:305 EASTERN AVE  
City:CHELSEA  
State:MA  
ZIP:02150-3344  
Country:US  
Info Phone Num:617-884-6918  
Emergency Phone Num:617-884-6918  
CAGE:65313  
=== Contractor Identification ===  
Company  
Name:GLYPTAL INC  
Address:305 EASTERN AVE  
Box:NONE  
City:CHELSEA  
State:MA  
ZIP:02150-3344  
Country:US  
Phone:617-884-6918  
CAGE:65313  
Company Name:THE SMITH GROUP INC.  
Address:811 E. CAYUGA STREET  
Box:City:PHILADELPHIA  
State:PA  
ZIP:19124-3893  
Country:US  
Phone:215-743-8200  
CAGE:2B613

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 34.5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100

PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:VARNISH MAKERS & PAINTER NAPHTHA  
CAS:8030-30-6  
Fraction by Wt: 5.6%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:STODDARD SOLVENT,  
CAS:64741-41-9  
Fraction by Wt: 0.2%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE  
CAS:1309-38-2  
RTECS #:OM4800000  
Fraction by Wt: 8.2%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:TALC  
CAS:14807-96-6  
RTECS #:MW2700000  
Fraction by Wt: 16.9%  
Other REC Limi  
ts:NONE RECOMMENDED  
OSHA PEL:0.2 FIBERS/CC  
ACGIH TLV:0.2 FIBERS/CC; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: IRRITATION, DEFATTING, DRYING, &  
DERMATITIS. EYES: IRRITATION. INHALATION: CENTRAL NERVOUS SYSTEM  
DEPRESSION, HEADACHES, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS.  
INGESTION: VOMITING, CHEMICAL  
PNEUMONITIS, & PULMONARY  
EDEMA/HEMORRHAGE.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:SKIN: IRRITATION, DEFATTING, DRYING, &  
DERMATITIS. EYES: IRRITATION. INHALATION: CENTRAL NERVOUS SYSTEM  
DEPRESSION, HEADACHES, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS.  
INGESTION: VOMITING, CHEMICAL PNEUMONITIS, & PULMONARY  
EDEMA/HEMORRHAGE.  
Medical Cond Aggravated by Exposure:PRE-EXISTING LIVER AND/OR KIDNEY  
DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

=====

===== First Aid Measures =====

First Aid:INGESTION: IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS, CAN CAUSE CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN OR CPR IF NEEDED. EYES:FLUSH W/PLENTY OF WATER. SKIN: WASH THOROUGHLY W/WATER. USE HAND LOTION. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====  
=====

Flash Point Method:PMCC  
Flash Point:72F  
Lower Limits:1%  
Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS W/POSITIVE PRESSURE MODE. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.  
Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO HEAT MAY CAUSE PRESSURE BUILD-UP. FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:USE AN ABSORBENT MATERIAL SUCH AS VERMICULITE TO REMOVE SPILLED MATERIAL. PROVIDE ADEQUATE VENTILATION.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, WELL-VENTILATED AREA. AVOID EXCESSIVE HEAT, SPARKS, & OPEN FLAMES. GROUND CONTAINERS & TRANSFER VESSELS.  
Other Precautions:KEEP FREE FALL OF LIQUID TO A FEW INCHES TO AVOID BUILD-UP OF STATIC ELECTRICITY. DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS USE AN APPROVED SELF-CONTAINED RESPIRATOR.  
Ventilation:KEEP AIR  
Spec Gravity:9.91 LB/GL  
Evaporation Rate & Reference: