

DAVIS-HOWLAND OIL CORPORATION -- VVD-1078 - 40000 CST DAMPING FLUID, SILICON --
9150-00-543-7219

===== Product Identification =====

Product ID:VVD-1078 - 40000 CST DAMPING FLUID, SILICON

MSDS Date:01/01/1987

FSC:9150

NIIN:00-543-7219

MSDS Number: BLFFT

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info

Phone Num:716-473-6651

Emergency Phone Num:716-473-6651

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENTS

Fraction by Wt

: 100% %

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:20,000 MG/KG ACUTE ORAL LD50 (RAT)

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:THIS PRODUCT OR ONE OF ITS INGREDIENTS
PRESENT 0.1% OR MORE IS NOT LISTED AS A CARCINOGEN BY NTP, IARC OR
OSHA.

Effects of O

verexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF
WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION IF
IRRITATION PERSISTS.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>400F,>204C

Lower Limits:NOT GIVEN

Upper Limits:NO

T GIVEN

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAP OR SOAK UP IN AN INERT MATERIAL
AND PUT IN A CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage

Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.
Ventilation:GENERAL (MECHANICAL) VENTILATION SHOULD BE ADEQUATE.
Protective Gloves:RUBBER GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT
AND BEFORE EATING
DRINKING OR SMOKING.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:NOT GIVEN
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN
Vapor Pres:NEGLIGIBLE
Vapor Density:NEGLIGIBLE
Spec Gravity:0.97
Evaporation Rate & Reference:> 1 (BUTYL ACETATE = 1)
Solubility in Water:INSOLUBLE
Appearance and Odor:CLEAR ODORLESS LIQUID
Percent Volatiles by Volume:< 1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
FORMALDEHYDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
Th

is information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.