View NSN Online: https://aerobasegroup.kr/nsn/5970-01-223-0782

HYSOL DIVISION, THE DEXTER CORP. -- PC18M -- 5970-01-223-0782

Product ID:PC18M MSDS Date:03/20/1990 FSC:5970 NIIN:01-223-0782 MSDS Number: BLHKD === Responsible Party === Company Name: HYSOL DIVISION, THE DEXTER CORP. Address:211 FRANKLIN ST. City:OLEAN State:NY ZIP:14760-1297 Country:US Info Phone Num:716-372-6300 Emergency Phone Num:716-372-6309 Preparer's Name:JA **MES P HORNBURG** CAGE:DO953 === Contractor Identification === Company Name: DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV Address:211 FRANKLIN ST. Box:City:OLEAN State:NY ZIP:14760-1297 Country:US Phone:716-372-6300/6309 CAGE:04347 Company Name: HYSOL DIVISION, THE DEXTER CORP. CAGE:DO953 Company Name: MCKEOWN ROBERT CO. INC. Address:111 CHAMBERS BROOK RD. Box:City:SOMERVILLE State:NJ ZIP:08876 Country:US Phone:908-218-9000 CAGE:7B953

======= Composition/Information on Ingredients =========

===

Ingred Name:URETHANE PREPOLYMER RESIN SOLUTION Fraction by Wt: 30-60% Other REC Limits:NONE SPECIFIED

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 15-20% Other REC Limits:NONE SPECIFIED OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III) CAS:100-41-4 RTECS #:DA0700000 Fraction by Wt: 5-10% Other REC Limits:NONE SPECIFIED OSHA PEL:100 PPM/125 STEL ACGIH TLV:100 PPM/125STEL 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHOXY PROPANOL ACETATE Fraction by Wt: 10-30% Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-EYES:MILD IRRITATION. SKIN:DEFATING,IRRITATION. INHALATION:RESPIRATORY IRRITATION, DIZZINESS, DROWSINESS AND UNCO
NSCIOUSNESS. INGESTION:DIGESTIVE SYSTEM IRRITATION, VOMITING. ASPIRATION OF LIQUI D INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS. CHRONIC-ALLERGIC SKIN REACTIONS, DERMATITIS.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:HEADACHE, NAUSEA, SHORTNESS OF BREATH, WEAKNESS, FATIGUE, VOMITING, EYE AND SKIN IRRITATION.

Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF SKIN AND

RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION:DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW KNEES. CALL PHYSICIONIMMEDIATELY.

Flash Point Method:T CC Flash Point:81F, (XYL) Lower Limits:1.0 Upper Limits:7.0 Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard: FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS. _____ Spill Release Procedures: CLEAN UP, OR ABSORB IN AN INERT MATERIAL, SAVE THE ABSORBENT IN A DISPOSAL CONTAINER. VENTILLATE THE AREA AND REMOVE SOURCES OF IGNITION. WEAR RESPIRATOR FOR ORGANIC VAPORS. Handling and Storage Precautions: STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM PHYSICA L DAMAGE. Other Precautions: AVOID EYE AND SKIN CONTACT. AVOID BREATHING VAPORS. PROVIDE SUFFICIENT VENTILATION. Respiratory Protection: NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR. Ventilation:LOCAL EXHAUST VENTILATION. Protective Gloves:NITRILE RUBBER GLOVES

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVO

ID PROLONGED OR REPEATED CONTACT. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

HCC:F3 Boiling Pt:=138.3C, 281.F B.P. Text:281F,138C Vapor Pres:9.5(XYL) Vapor Density:3.7(XYL) Spec Gravity:1.02 Evaporation Rate & amp; Reference:0.54 (BU AC = 1) (XYL) Solubility in Water:NEGLIGIBLE Appearance and Odor:LIGHT AMBER MEDIUM VISCOSITY LIQUID, AROMATIC ESTER SOLVENT ODOR. Percent Volatiles by Volume:50

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE, POSSIBLE NITROGEN OXIDES.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume re sponsibility for the suitability of this information to their particular situation.